

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office \_\_\_\_\_  
Lease No. **Jicarilla #132**  
Unit \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<b>X</b>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 16, 1963


**Florance-Humble**  
Well No. **1** is located **1650** ft. from **[N]** line and **990** ft. from **[W]** line of sec. **5**  
**SW 1/4 Section 5** **22N** **2W** **R4PM**  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
**Cuba Block** **Sandoval** **New Mexico**  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Abandoned well as follows: Cement plug from 2872' to 2700' w/15 sz. Shoot 4 1/2" casing at 513'. Pulled 19-jts. of 4 1/2" casing (512.66'). Cement plug from 563' to 463' w/16 sz., and 10 sz. cement in top of surface. A regulation dry hole marker erected. Ready for inspection.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Humble Oil & Refining Company**  
Address **P. O. Box 3082**  
**Durango, Colorado**  
By **COPI (ORIGINAL SIGNED) B. M. SPARLEY**  
Title **Dist. Supt.**