

MAR 12 1956

APPROVED

(Orig)

Sgd.) J. W. LONG

DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYIndian Agency San JoseContract No. 54Allottee Tract No. 104Lease No. MS-10611

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL <u>no cement</u> <u>no cement</u> <u>no cement</u>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 16

19 56

Well No. D-1 is located 790 ft. from N line and 790 ft. from W line of sec. 33
SE 1/4 NW 1/4 of 33 T-23-N R-3-W MTN
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat Sandoval County New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 7229 ft. ground level

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

A total depth of 7190 feet was reached in an 8 1/4-inch hole on February 10, 1956. On February 14, 1956 verbal permission was received from Mr. Long of the U. S. Geological Survey office, Farmington, New Mexico, to plug and abandon this well in the following manner: 30 sacks cement from 7100 to 7190 feet, 30 sacks cement from 6800 to 6890 feet, 30 sacks cement from 6400 to 6490 feet, 30 sacks cement from 6000 to 6090 feet, 30 sacks cement from 5600 to 5690 feet, 30 sacks cement from 5200 to 5290 feet, 30 sacks cement from 4800 to 4890 feet, 30 sacks cement from 4400 to 4490 feet, 30 sacks cement from 4000 to 4090 feet, 30 sacks cement from 3600 to 3690 feet, 30 sacks cement from 3200 to 3290 feet, 30 sacks cement from 2800 to 2890 feet, 30 sacks cement from 2400 to 2490 feet, 30 sacks cement from 2000 to 2090 feet, 30 sacks cement from 1600 to 1690 feet, 30 sacks cement from 1200 to 1290 feet, 30 sacks cement from 800 to 890 feet, and 10 sacks in bottom of 10 1/4-inch surface casing at 400 to 410 feet, and 10 sacks in top of 10 1/4-inch surface casing. An appropriate sign and marker will be placed at the well site. The location will be restored as nearly as possible to its original status and the U. S. Geological Survey office in Farmington, New Mexico will be notified of the completion date. No commercial shows of oil or gas were encountered during the drilling of this well. All measurements being from Kelly bushing which is 14 feet above ground level.

I understand that this plan of work must receive approval in writing by the Geological Survey before operation.

Company Reynolds Mining Corporation
Oil and Gas Division
Address 132 1/2 East 9th Street
P.O. Box 1300
Durango, Colorado

By C. J. [Signature]
Title District Petroleum Engineer



