

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> X OTHER		5. LEASE DESIGNATION AND SERIAL NO. Jicarilla Cont 54	
2. NAME OF OPERATOR Meridian Oil Inc.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jic. Tribe	
3. ADDRESS OF OPERATOR Post Office Box 4289, Farmington, NM 87499		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 790'N, 790'E		8. FARM OR LEASE NAME Stromberg	
14. PERMIT NO.		9. WELL NO. 5	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7267'GL		10. FIELD AND POOL, OR WILDCAT Ballard Pic. Cliffs	
		11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA Sec. 34, T-23-N, R- 3-W N.M.P.M.	
		12. COUNTY OR PARISH Sandoval	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☒
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

FRACTURE TREATMENT

REPAIRING WELL

SHOOTING OR ACIDIZING

ALTERING CASING

(Other)

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

It is intended to plug this well in the following manner:

MOL&RU. Pull 2 3/8" tbgs. to release packer and TOOH. TIH w/2 3/8" to 2845'. Spot 55 sx. cement to cover the Pic.Cliffs perfs for a plug from 2900-2262' (Ojo Alamo-2425' - top of cement 2415'-75% calc).

WOC 6 hrs. Tag plug and record top. Circulate 37 bbls. of 9.2# mud. Perforate 2 squeeze holes 50' below the base of the surface casing @ 148'. Circulate 45 sx. cement from surface and out bradenhead. Cut off wellhead and set dry hole marker w/10 sx. cement.

RECEIVED
APR 14 1988

OIL CON. DIV.
APPROVED

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE Drilling Clerk(CS)

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

04-05-88

APR 06 1988

DATE

AREA MANAGER

FARMINGTON RESOURCE AREA

*See Instructions on Reverse Side