

**Santa Fe, New Mexico**

NUMBER OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
TRANSPORTER	OIL GAS	
PRORATION OFFICE		
OPERATOR		

## WELL RECORD

$\circ$ E      10

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in **QUINTUPLICATE** If State Land submit 6 Copies

**AREA 040 ACRES  
LOCATE WELL CORRECTLY.**

**TEXACO Inc.**

**Howard Major**

(Company or Operator)

(Leave)

Well No. 1, in SW  $\frac{1}{4}$  of NW  $\frac{1}{4}$ , of Sec. 10, T. 13 North, R. 3 West, NMPM  
**Wildcat** Pool Sandoval County

Well is 2040 feet from North line and 680 feet from West line

of Section 10 If State Land the Oil and Gas Lease No. is -

Drilling Commenced May 10, 1964 Drilling was Completed June 10, 1964

Name of Drilling Contractor Pico Drilling Company

Address 3800 Sunset Drive, Farmington, New Mexico, 87401

Elevation above sea level at Top of ~~Platform~~ Derrick Floor 6243. The information given is to be kept confidential until  
19

### OIL SANDS OR ZONES

No. 1. from **Dry hole** to ..... No. 4. from ..... to .....

No. 2, from..... to..... No. 5, from..... to.....

No. 3, from.....to..... No. 6, from.....to.....

## IMPORTANT WATER SANDS

**Include data on rate of water inflow and elevation to which water rose in hole.**

No. 1, from none to feet.

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

No. 4, from ..... to ..... feet.

### CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
10-3/4"	32.75	new	590'	Baker	None	-	-

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13-3/4"	10-3/4"	603'	210	Dowell	-	-

### RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

**Dry hole**

### Result of Production Stimulation

## ..Depth Cleaned Out.

# RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

## TOOLS USED

Rotary tools were used from 0 feet to 6387 feet, and from - feet to - feet.  
Cable tools were used from - feet to - feet, and from - feet to - feet.

## PRODUCTION

Put to Producing **Dry hole**, 19

OIL WELL: The production during the first 24 hours was - barrels of liquid of which - % was oil; - % was emulsion; - % water; and - % was sediment. A.P.I. Gravity -

GAS WELL: The production during the first 24 hours was - M.C.F. plus - barrels of liquid Hydrocarbon. Shut in Pressure - lbs.

Length of Time Shut in -

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

### Southeastern New Mexico

### Northwestern New Mexico

T. Anhy.	T. Devonian.	T. Ojo Alamo.
T. Salt.	T. Silurian.	T. Kirtland-Fruitland.
B. Salt.	T. Montoya.	T. Farmington.
T. Yates.	T. Simpson.	T. Pictured Cliffs.
T. 7 Rivers.	T. McKee.	T. Menefee.
T. Queen.	T. Ellenburger.	T. <del>Redondo</del> <b>1154</b>
T. Grayburg.	T. Gr. Wash.	T. <del>Marathon</del> <b>1170</b>
T. San Andres.	T. Granite.	T. <del>Chinle</del> <b>1472</b>
T. Glorieta.	T.	T. <del>Glorieta</del> <b>2850</b>
T. Drinkard.	T.	T. <del>Yeso</del> <b>3074</b>
T. Tubbs.	T.	T. <del>Abo</del> <b>4400</b>
T. Abo.	T.	T. <del>Nader</del> <b>5075</b>
T. Penn.	T.	T. <del>Sandia</del> <b>6080</b>
T. Miss.	T.	T. <del>Pre-Cambrian</del> <b>6275</b>

## FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	2660		Sand and Shale	DST #1, 4900'	5007'		Tool open 1½ hours with a weak blow of air. Recovered 660' of fresh water cut drilling mud. No show of oil or gas.
2660	2768		Shale and Lime				
2768	3005		Sand, Shale & Lime				
3005	5323		Sand and Shale				
5323	5430		Sand, Shale & Lime				
5430	5592		Sand and Shale				
5592	5772		Sand, Shale & Lime				
5772	5900		Sand and Shale				
5900	6095		Sand, Shale & Lime				
6095	6148		Sand, Shale, Lime & Chert				
6148	6387		Sand, Shale & Lime				
Total Depth			6387'				
All measurements from derrick floor, 13' above ground level.							

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

August 19, 1964

(Date)

Company or Operator **TEXACO Inc.**

Address **P.O. Box 810, Farmington, New Mex.**

Name **G. L. Eaton**

Position or Title **Acting District Supt. 87401**