

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency Mescalito Apache
Allottee _____
Lease No. 25 Contract

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	OCT 5 1959
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)


Well No. Mescalito 25-2 is located 990 ft. from N line and 825 ft. from E line of sec. 35
SW SW Sec. 35 23N 3E R24W
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 7227 ft. R.D.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total Depth: 2845' P.H.T.D. 2830'
Casing: 4 1/2" 9.30 cemented at 2845'
Perforations: 2725' - 64', 2770' - 73'
9-20-59: Acidized with 300 gallons mud acid. Maximum pressure 2000/2000, final pressure 60/2000.
9-20-59: Fractured well down casing with 10,000 gallons water and 10,000 sand, maximum & final pressure 11000, on vacuum in 25 minutes.
2 1/2" long 2777', packer at 2701'
9-20-59: Flowed 1374 MCF per day rate.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The Superior Oil Company
Address P. O. Box 6
Cortez, Colorado

By D. D. Kingman
S. A. Kingman
Title Engineer