

November 4, 1968

T. J. Krestschman and Arwood Stowe
Well No. Ellisberry #1
Section 30 17N 3W Sandoval County, New Mexico
490' from the West line & 800' from the North line
ground elevation 6363'

Rotary
C & M Drilling Company, Contractor

Point Lookout 420'
Gallup 1350'

Surface Plug
4' Marker

375-475-275
Plug

100 to 140	Sandstone bentonitic tight
140 170	shale green
170 180	shale pale green
180 190	sandstone
190 200	sandstone light gray hard tight
200 210	sandstone tan to brown
210 220	shale gray trace coal
220 230	sandstone white to light gray
230 250	shale
250 270	shale
270 280	sandstone light gray bentonitic clay
280 330	shale
330 340	coal
340 360	shale
360 380	sandstone, white to gray bentonitic
380 400	shale gray
400 410	coal
410 430	sandstone ——— + 6363
430 450	shale gray sandy + 295
450 480	sandstone
480 490	coal
490 500	shale
500 520	sandstone light gray dense tight
520 990	shale
990 1000	siltstone
1000 1100	shale medium gray sandy
1100 1120	siltstone light gray shaly
1120 1240	siltstone light gray (no shows)
1240 1280	shale gray sandy
1280 1350	shale light gray traces of limestone
1350 1370	sandstone light gray
1370 1400	siltstone light gray
1400 1440	sandstone light gray (no shows)
1440 1440	shale dark gray sandy traces of limestone
1440 1450	sandstone dark gray (no shows)
1450 1460	siltstone light gray tight
1460 1470	shale and sand
1470 1500	shale dark gray
	<u>TOTAL DEPTH</u>

375 PLO

6363
4352
- 75013

RECEIVED

APR 26 1969

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

November 4, 1968

T. J. Krentschman and Arwood Stowe
Well No. Ellsberry #1
Section 30 17N 3W Sandoval County, New Mexico
490' from the West line & 800' from the North line
ground elevation 6363'

Rotary
C & M Drilling Company, Contractor

Point Lookout 4200'
Gallup 1350'

100 to 140 Sandstone bentonitic tight
140 170 shale green
170 180 shale pale green
180 190 sandstone
190 200 sandstone light gray hard tight
200 210 sandstone tan to brown
210 220 shale gray trace coal
220 230 sandstone white to light gray
230 250 shale
250 270 shale
270 280 sandstone light gray bentonitic clay
280 330 shale
330 340 coal
340 360 shale
360 380 sandstone, white to gray bentonitic
380 400 shale gray
400 410 coal
410 430 sandstone — + 6363
430 450 shale gray sandy + 5953
450 480 sandstone
480 490 coal
490 500 shale
500 520 sandstone light gray dense tight
520 990 shale
990 1000 siltstone
1000 1100 shale medium gray sandy
1100 1120 siltstone light gray shaly
1120 1240 siltstone light gray (no shows)
1240 1280 shale gray sandy
1280 1350 shale light gray traces of limestone
1350 1370 sandstone light gray
1370 1400 siltstone light gray
1400 1410 sandstone light gray (no shows)
1410 1440 shale dark gray sandy traces of limestone
1440 1450 sandstone dark gray (no shows)
1450 1460 siltstone light gray tight
1460 1470 shale and sand
1470 1500 shale dark gray

TOTAL DEPTH

RECEIVED

APR 23 1969

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

6363
5953
4610

No Electric Log Run

Plugged Well - Cement
10' plug in top & MARKER
275' - 475'
1275' - TD.

Instructions were to
plug 1275' to TD
375' to 475' - had fill up
to 275'

Surface Plug
at Marker

375' - 475' - 275'

Plug
1275'
to TD

November 4, 1968

T. J. Krentschman and Arwood Stowe
Well No. Ellisberry #1
Section 30 17N 3W Sandoval County, New Mexico
490' from the West line & 800' from the North line
ground elevation 6363'

Rotary
C & M Drilling Company, Contractor

Point Lookout 420'
Gallup 1350'

375-475' 275'
710' 275'
Play 1275' to TD

100 to 140	Sandstone bentonitic tight
140 170	shale green
170 180	shale pale green
180 190	sandstone
190 200	sandstone light gray hard tight
200 210	sandstone tan to brown
210 220	shale gray trace coal
220 230	sandstone white to light gray
230 250	shale
250 270	shale
270 280	sandstone light gray bentonitic clay
280 330	shale
330 340	coal
340 360	shale
360 380	sandstone, white to gray bentonitic
380 400	shale gray
400 410	coal
410 430	sandstone — + 6363
430 450	shale gray sandy 375 275
450 480	sandstone
480 490	coal
490 500	shale
500 520	sandstone light gray dense tight
520 990	shale
990 1000	siltstone
1000 1100	shale medium gray sandy
1100 1120	siltstone light gray shaly
1120 1240	siltstone light gray (no shows)
1240 1280	shale gray sandy
1280 1350	shale light gray traces of limestone
1350 1370	sandstone light gray
1370 1400	siltstone light gray
1400 1410	sandstone light gray (no shows)
1410 1440	shale dark gray sandy traces of limestone
1440 1450	sandstone dark gray (no shows)
1450 1460	siltstone light gray tight
1460 1470	shale and sand
1470 1500	shale dark gray
	<u>TOTAL DEPTH</u>

6363
1337
7501.3

RECEIVED
APR 26 1969
U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NE 0558479

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal

9. WELL NO.

41

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 30 17N 3E

12. COUNTY OR PARISH

Sandoval

13. STATE

New Mexico

1.

OIL WELL ☐ GAS WELL ☐ OTHER

Dry Hole

2. NAME OF OPERATOR

T. J. Kreatschman and Arwood Stowe

3. ADDRESS OF OPERATOR

PO Box 2265, Wichita Falls, Texas 76307

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

490' from the West line and 800' from the North line

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6363 01

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10' Cement plug in top and marker placed

Cement plug from 475' to 275'

Cement plug 1275' to TD



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE **Operator**

DATE **4-23-69**

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:



*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of packing of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.