

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau N. 42-P1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM 0558679

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Federal B

8. FARM OR LEASE NAME

#2

9. WELL NO.

Wildcat

10. FIELD AND POOL, OR WILDCAT

Sec. 22, 17N 3W

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

12. COUNTY OR PARISH

Sandoval

13. STATE

New Mexico

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR

T.J. Kretschman and Alwood Stowe

3. ADDRESS OF OPERATOR

P.O. Box 2265, Wichita Falls, Texas 76307

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

1620' from East Line and 2000' from South Line

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6417 GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

FULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*


Pulled all drill pipe out of hole entered with string of tubing and pumped cement in well as follows:

1300' to 1500' (TD) across sands in middle member of Gallup
260' to 360' across upper member of Gallup.
0' to 100' Surface plug (since surface casing was not set)

Marker set.

Heavy drilling mud was left between all cement plugs.

Well was plugged April 28, 1969



18. I hereby certify that the foregoing is true and correct

SIGNED

Alwood Stowe

TITLE

Operator

DATE

May 23, 1974

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

T.J. Kreatschman and Arwood Stowe
Federal "B"
Section 22 17N 3W
Sandoval County, New Mexico

Ground elevation 6417'

Rotary
C&M Drilling Company, contractor

0	to	110	sh sd stone
110	to	120	sd stone
120	to	130	coal
130	to	140	sh
140	to	150	sd stone
150	to	160	sh
160	to	170	coal
170	to	260	sd stone (180 to 190 oil stain - floors)
260	to	270	no samples
270	to	280	siltstone and sh
280	to	310	sd stone no show
310	to	320	sh
320	to	350	siltstone
350	to	400	sh
400	to	500	sh
500	to	600	sh sdy bentonitic
600	to	700	sh
700	to	740	sh
740	to	750	siltstone tight
750	to	780	sh gray sdy
780	to	800	siltstone tight
800	to	900	sh gray sdy hard
900	to	1060	siltstone shy hd dense
1060	to	1090	siltstone "salt & pepper" sdy
1090	to	1130	sh and siltstone
1130	to	1210	siltstone thin sdy sh partings
1210	to	1290	sh sdy
1290	to	1340	siltstone
1340	to	1350	sh
1350	to	1360	sdstone white (spoty oil stains) dense tight
1360	to	1400	sh dark gray sdy
1400	to	1487	SH
1487	to	1500	SH



TOTAL DEPTH

No Electric Log run