

November 18, 1968

T. J. Kreatschman and Arwood Stowe
Well No. "C" Mike # 1
Section 13 17N 3W Sandoval County, New Mexico
1000' from the South line
1980' from the East line
Ground Elev. 6422'

Rotary
C & M Drilling Company, Contractor

Surface
Plug

Plug
100-200

100	to 110	Sandstone	
110	120	Coal and Sandstone	
120	140	Siltstone and Bentonite	
140	180	Sandstone, Siltstone	
		(Light tan oil show, oil fluorescence)	+ 6282
180	210	Bentonite & Shale	
240	260	Sandstone & Shale	
260	300	Sandstone, <u>TOP POINT LOOKOUT</u>	
		(tan oil stain, oil fluorescence)	+ 6182
		(fill on pits)	
300	360	Sandstone (no oil show)	
360	460	Sandstone, Shale & Siltstone	
460	480	Sandstone	
480	520	Sandstone & siltstone	
520	540	Sandstone	
540	600	Sandstone & Siltstone	
600	900	Siltstone & sandstone	
900	920	Sandstone	
920	1000	Sandstone & Siltstone	
1000	1020	Sandstone & Siltstone (thin coal streak)	
1020	1040	Sandstone & Siltstone	
1040	1050	Siltstone	
1050	1070	Sandstone & Siltstone	
1070	1090	Sandstone & Siltstone (coal streak)	
1090	1140	Sandstone & siltstone <u>TOP GALLUP SANDSTONE</u>	+ 5332'
1140	1170	Sandstone, Siltstone & Shale	
1170	1200	Sandstone, Siltstone & Shale	
		(Dead oil stain, spotty light oil stain and fluorescence.)	+ 5252'
1200	1210	Sandstone, Siltstone & Shale	
1210	1230	Sandstone, Siltstone & Shale	
1230	1250	Sandstone, Siltstone & Shale	

Plug
1040
to
1250

TOTAL DEPTH

NO Electric Log run

Instructions were
Plug from 1090' to
TD but had fillup
to 1040'

Plugged well - Cement
10' plug in top & marker
Plug 100' to 200'
Plug 1040 to 1250'