

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 045884-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Federal

7. UNIT AGREEMENT NAME

None

8. FARM OR LEASE NAME

Federal Media

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Media Pool

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 22, T19N, R3W

12. COUNTY OR PARISH

Sandoval

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

DON C. WILEY and FLUID POWER PUMP COMPANY

3. ADDRESS OF OPERATOR

1116 Bank of New Mexico Building, Albuquerque, N. M. 87101

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

430° FNL, 1690' FEL

14. PERMIT NO.

USGS 5/2/69

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6866 GR, 6878 KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) **Plug Back and Run Casing** ☒

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plug back and run casing per telephone approval by U.S.G.S. May 16, 1969:
Set plug at 5300 w/60 sks regular cement from 5342' - 5100', 242' Entrada Sandstone.
Set plug at 4445' w/87 sks regular cement from 4445' - 4145', 300' Dakota Sandstone.
Set 3108' of 4-1/2" casing at 3102' K.B. and cemented with 175 sks Class "C" Cement, 175 sks Diamix "A" Cement. Cemented from 3108' to 1150'.
Tested behind plug w/2000 lbs. Held okay.

Work completed May 16, 1969.
, 9:45 p.m.

Copies: 5 to U.S.G.S.
1 to Malcolm Colberg
1 to Don C. Wiley
1 to Loffland Bros. Drilling Co.



18. I hereby certify that the foregoing is true and correct

SIGNED

W. E. Riley

TITLE

Geologist

DATE **May 16, 1969**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

DATE

MAY 20 1969

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.