

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR  
BCO, Inc.

3. ADDRESS OF OPERATOR  
135 Grant Avenue Santa Fe, NM 87501

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface  
2060' FSL 660' FEL Sec. 22 T23N R7W NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, ST, GR, etc.)  
7175 GR

RECEIVED

JUN 08 1987

5. LEASE DESIGNATION AND SERIAL NO.  
NM-6682

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Federal B

9. WELL NO.  
22

10. FIELD AND POOL, OR WILDCAT  
Lybrook Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
22-23N-7W NMPM

12. COUNTY OR PARISH  
Sandoval

13. STATE  
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

May 11, 1987 Pull 2 3/8" tubing. Trip in hole with casing scraper.

May 12, 1987 Set bridge plug at 5550'. Set model H straddle packers at 5414-5378'. Spotted gel between packers. Halliburton frac valve leaking so unable to frac well.

May 13, 1987 Treated 30,000 gallons of water with 130 gallons TRI-S, 60 gallons of 3N, 5600 lbs of KCL, 30 gallons LP55 scale check, 600 lbs WG-11, 76 lbs HYG-3, 76 lbs K-35 and 3 lbs GBW-30. Sand water foam fracked 5497'-5520' with 83,340 gallons of 70% foam, 106,500 lbs of 20-40 sand, 1,406,100 standard cubic feet of nitrogen. Average treating pressure 4500 lbs at 20 foam barrels per minute. ISIP 2300, 5 min 1990, 10 min 1970, 15 min 1930. Flowed well back.

May 14, 1987 Well flowing. Killed well. Released packers. Circulated hole clean. Could not catch bridge plug. Pulled out of hole with 2 7/8" tubing and straddle packer. Went in hole with retrieving tool. Caught bridge plug. Rigged up swab equipment. Swabbed.

May 15, 1987 Swabbed well

May 16, 1987 Swabbed well

RECEIVED  
JUN 11 1987  
OIL CON. DIV.  
DIST. 2

18. I hereby certify that the foregoing is true and correct

SIGNED Elizabeth B. Keeshan

TITLE Comptroller

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE JUN 09 1987

FARMINGTON RESOURCE AREA

BY sm

\*See Instructions on Reverse Side

NMOCO

CONTINUED

Page 2

SUNDRY NOTICE

Lease No. NM-6682

Federal B

#22

Sec. 22-23N-7W NMPM

Sandoval, NM

---

May 18, 1987 Laid down 2 7/8" tubing. Tripped in hole with 2 3/8" tubing. Tagged sand at 5573'. Cleaned out sand to 5656'. Landed 2 3/8" tubing at 5592'. Circulated hole. Kicked well off with 100,000 standard cubic feet of nitrogen.

May 19, 1987 Swabbed well. Kicked off well. Dropped piston. Placed well back in production.