

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Contract No. 373

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla

7. UNIT AGREEMENT NAME

None

8. FARM OR LEASE NAME

Cuba Pan Am

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated Gallup

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 24, T22N-R3W, NMPM

12. COUNTY OR PARISH

Sandoval

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	
2. NAME OF OPERATOR REFINERS PETROLEUM CORP.	
3. ADDRESS OF OPERATOR 900 Bank of New Mexico Building, Albuquerque, New Mexico 87102	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 990' FSL, 1650' FWL	
14. PERMIT NO. USGS 10-28-70	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7246' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING


ABANDONMENT*

(Other) Supplemental

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set bridge plug at 6300' to shut off Dakota. Ran cement bond log and found top of cement 300' above Gallup formation. Perforated 5560-62', 5574-76', 5602-03', 5609-11', 5615-20', 5648-50', 5660-5662', 5686-92', 5704-06', 5743-47', 5752-54', 5768-70', 5786-96', 5806-14', 5826-30', 5640-46', 5878-90', 5914-20', 5932-38', 5952-56', 5990-6000' (total of 95') with 2 shots per foot. Sand/water fractured using 30,000 gallons water and 40,000# sand. Dropped 150 balls. Ran tubing, swabbed well, recovered approximately 60 barrels new oil, decreasing to trace of oil. Re-ran rods and tubing. Started pumping to clean up Gallup 8-9-74. Downhole pump stuck on 8-11-74. Shut well in, waiting on pulling unit.



18. I hereby certify that the foregoing is true and correct

SIGNED

Morris B. Jones

TITLE

Petroleum Engineer

DATE

5-22-74

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.