## **UNITED STATES** DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

SUBMIT IN TRIPLICATE\*

Form approved: Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

CEOL	OCICAL	. SURVEY
GEUL	JOILAL	JUILVEI

<b>JNDRY</b>	<b>NOTICES</b>	AND	REPORTS	ON	WELLS

IP.	INDIA	м,	AL	POJ	TEE	UK	THI	81	N A	м
		- 1	7.	-	20		<b>&gt;</b> :			
			.,,		- 7			~*	-	
	53	Ξ.	4	(N)	9		Ξ.	<u>~</u>		
								-		

N.M. 0555225

(Do not use this form for propos	ICES AND REPORIS ON WELLS sals to drill or to deepen or plug back to a different reservoir. ATION FOR PERMIT—" for such proposals.)	The state of the s
OIL GAS OTHER	Dry	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Sun Oil Company		8. FARM OR LEASE NAME Sandoval-Federal
3. ADDRESS OF OPERATOR P. O. Box 1861 Mi	dland, Texas 79701	9. WELL NO. 16 CO STATE OF THE PROPERTY OF THE
<ol> <li>LOCATION OF WELL (Report location c See also space 17 below.)</li> <li>At surface</li> </ol>	learly and in accordance with any State requirements.*	10. FIELD AND POOL, OR WILDCAT Wildcat
330' FNL and 2310'	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  Sec. 24, Twp. 18N, Rge 3W	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
Approved 5/25/71	6562.0 GR	Sandoval New Mexico
16. Check Ar	ppropriate Box To Indicate Nature of Notice, Report, a	r Other Data = 5 = 5 = 5 = 5

NOTICE OF INTENTION TO:					
		DULL OF LETTER GLOSVO			
TEST WATER SHUT-OFF		PULL OR ALTER CASING			
FRACTURE TREAT		MULTIPLE COMPLETE			
SHOOT OR ACIDIZE		ABANDON*			
REPAIR WELL		CHANGE PLANS			

REPAIRING WELL WATER SHUT-OFF ALTERING CASING FRACTURE TREATMENT ABANDONMENT\* (Other) (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Current hole conditon: 8 5/8" csg. seated @ 3539; 7 7/8" open hole 3539-8750.

7/10/71

(Other)

Spot cement plugs as follows:

8650-8750, 35 sx Class C, 50-50 Pozmix, 1/2% HR-4.

8150-8300, 50 sx Class C, 50-50 Pozmix, 6475-6650, 55 sx

4525-4725, 60 sx 3500-3600, 50 sx. Top 8 5/8", 15 sx.

8 5/8- 13 3/8 annulus, 5 sx.

Set dry hole marker.

Pipe left in hole:

13 3/8 -380 8 5/8 -3529 OIL CON. DIST.

18. I hereby certify that the rosegoing is true and correct July 30, 1971 Sr. Admin. Clerk SIGNED DATE (This space for Federal or State online 2001) ionte ionte onte RIFE, I or I APPROVED BY TITLE DATE CONDITIONS OF APPROVAL, IF ANY: 60114 abor Metical 1008 2001 2001

\*See Instructions on Reverse Side