

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

424

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Littleton

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 8-T22N-R5W
N. M. F. M.

12. COUNTY OR PARISH 13. STATE

Savdoval

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Warren Drilling Company

3. ADDRESS OF OPERATOR
1215 United Founders Tower, Oklahoma City, Oklahoma 73100

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

660' FNL & 660' FWL. Sec. 8-T22N-R5W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6992' K. B.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 6-4-71

6-4-71 T. D. 264'

Ran 8 joints, 8 5/8", 24.0 lb. J-55, T&C Casing (251.40')
Set at 262' with 150 sacks class "A" cement with
3% Calcium Chloride Tested O. K. with 500 psig.

6-22-71 P. B. T. D. 5230'

Ran 159 joints, 4 1/2", 9.50 lb, K-55, T&C casing (5091.06')
Set at 5102.06 with first stage 112 cubic feet 50/50 Pozmix
, "A" cement, second stage (stage tool at 4166') with Cubic
feet 50/50 Pozmix "A" Baker Triplex Shoe on bottom. Tested
O. K. with 2000 psig.



RECEIVED

JUN 30 1971

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

18. I hereby certify that the foregoing is true and correct

SIGNED

Walsh Engr. & Prod. Corp.

TITLE

President

Walsh Engr. & Prod. Corp.

DATE

6-29-71

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

St.