

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. NAME OF OPERATOR
~~North American Exploration Co. & Lesoro Petroleum Corporation~~
3. ADDRESS OF OPERATOR
408 First State Bank Bldg., Abilene, Texas 79601
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
990' FWL & 790' FWL Section 8, 119N R4W

14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.)
6701 GL, 6714 KE

5. LEASE DESIGNATION AND SERIAL NO.
USA - NM 7508A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
-
7. UNIT AGREEMENT NAME
-
8. FARM OR LEASE NAME
Encino
9. WELL NO.
1
10. FIELD AND POOL, OR WILDCAT
-
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 8
12. COUNTY OR PARISH
Sandoval
13. STATE
N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

DST #1 Menefee Sand 2162-2280 open 90" rec. 310' Drlg mud & 1308' brackish water
FP 171-847# SIP 764#. DST #2 Point Lookout Sand 2281'-2318' open 90" rec. 90' drlg mud
FP 13-40# SIP 764#. DST #3 Dakota Sand 4465-4540 open 60" rec. 50' drlg mud & 470'
fresh water 30" ISI 1695# FP 53-133# SIP 60" 1642#. TD 4719'.

TOPS Kch 822, Kmn 876, Kpl 2310, Kg 3480, Kgh 4255, Kgr 4297, Kdl 350, Jm 4670

No commercial oil or gas production. Preparing to abandon by filling hole with
10# drilling mud, with cement plugs as follows: 35 sx top Kd 4300-4400, 50 sx top Kg
3350-3500, 35 sx top Kpl 2200-2300, 35 sx in Kmv 500-600, 35 sx base of surface
casing 200-300, 10 sx at surface 0-30, with standard pipe marker.

to be plugged 11 Sep 71 with verbal approval



18. I hereby certify that the foregoing is true and correct

SIGNED

Gordon H. Gray

TITLE

Project Engineer

DATE

11 Sep 71

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.