

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER		5. LEASE DESIGNATION AND SERIAL NO. # 420
2. NAME OF OPERATOR North American Exploration Co. * Tesoro Petroleum Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache Tribal
3. ADDRESS OF OPERATOR 408 First State Bank Bldg., Abilene, Texas 79604		7. UNIT AGREEMENT NAME -
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1850' FNL & 890' FNL Sec. 29, 122N R3E		8. FARM OR LEASE NAME Parlay
14. PERMIT NO. Verbal		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7069 GL, 7081 AB		10. FIELD AND POOL, OR WILDCAT Wildcat
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 29 122N R3E
		12. COUNTY OR PARISH Sandoval
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 12 1/4" hole to 274, ran 8 joints 8 5/8" OD 24# K-55 surface casing, set at 269 KB, cemented with 200 sacks Howell Class A regular plus 2% calcium chloride cement. Plug down 4:30 P.M. 21 Aug 71. WOI 16 hours, pressure test to 650 psig., no pressure drop in 30 minutes. Drilled out from surface 2:30 P.M. 22 Aug 71. Cement weight 16 #/Gal., mixing temp. 80°F, estimated bottom hole temp. 70°F. Estimated compressive strength at test 1700 psi., at drill out 2600 psi.



AUG 25 1971

18. I hereby certify that the foregoing is true and correct

SIGNED

Gordon H. Gray
Gordon H. Gray

TITLE

Project Engineer

DATE

23 Aug 71

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for special instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.