

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well ☒ Oil Well ☐ Gas Well ☐ Other <u>LA Quinta Oil</u>	5. Lease Designation and Serial No. <u>Terminated</u>
2. Name of Operator <u>BIA AGENCY - Jicarilla</u>	6. If Indian, Allotment or Tribal Name <u>Jicarilla</u>
3. Address and Telephone No. <u>PO Box 167, Dulce, NM 87528</u>	7. If Unit or CA, Agreement Designation
4. Location of Well (Range, Sec., T., R., M., or Survey Description) <u>SE NE 1850 FNL, 890 FEL, Sec 29, T22N, R3W</u>	8. Well Name and No. <u>#1 Parley 20075</u>
	9. API Well No. <u>3004920086081</u>
	10. Field and Pool, or Exploratory Area
	11. County or Parish, State <u>Sandoval, NM</u>

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
☐ Notice of Intent	☒ Abandonment
☒ Subsequent Report	☐ Reconception
☒ Final Abandonment Notice	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☐ Other
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut-Off
	☐ Conversion to Injection
	☐ Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and major pertinent to this work.)

Set cement retainer @ 4283'. Pressured tested csg. to 200 psi. OK. Spotted 12 sxs of cement on retainer. Perfed 4spf 2236', 966' and 319'.

Set retainer @2186'. Attempted to pump into perfs. Pressured up to 1500 psi twice with no fluid movement. Pull out of retainer, and spot 36 sx on top of retainer.

Set retainer 916'. Cement with 34 sxs cement. Pull out of retainer leaving 7 sxs on top of retainer.

Cement from 319' to surface with 115 sx cement. Cement returns between 4.5 and 8 5/8" casing. Placed dry hole marker. Rehabilitate location

14. I hereby certify that the foregoing is true and correct.

Signed Ken Youngman BIA Reelstate Date 2/10/02

(This space for Operator or BLM Office Use)

Approved by [Signature] Title Ken E. [Signature] Date 3/10/02

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations or to any officer within its jurisdiction.

*See instructions on Reverse Side

** TOTAL PAGE. 03 **

FEB 27 1999 10:45