

Form 3160-3
(June 1992)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well ☒ Oil Well ☐ Gas Well ☐ Other	LA Quinta Cell
2. Name of Operator	BIA Jicarilla Agency
3. Address and Telephone No.	PO Box 167, Dulce, NM 87528
4. Location of Well (Range, Sec., T., R., or Survey Description)	2310 N + E SE 1/4 1850 FNL, 890 FEL, Sec 29, T 22N, R 3W
5. Well Name and No.	2 Parley 20084
6. API Well No.	3004920080051
7. If UMI or CA, Agreement Designation	
8. If Indian, Abandon or Tribe Name	Jicarilla
9. Field and Pool, or Exploratory Area	
10. County or Parish, State	Sandoval, NM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
☐ Notice of Intent	☒ Abandonment
☐ Subsequent Report	☐ Recompletion
☒ Final Abandonment Notice	☐ Plugging Back
	☐ Casing Repair
	☐ Alleviating Casing
	☐ Other
	☐ Change of Plans
	☐ New Completion
	☐ Non-Routine Preserving
	☐ Water Shut-IN
	☐ Conversion to Injection
	☐ Dispose Water

(Note: Report depths of multiple completion or Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Set cement retainer @ 4123'. Pressured tested csg. to 200 psi. OK. Spotted 12 sxs of cement on retainer.

Perfed 4spf 2260', 999' and 285'.

Set retainer @ 2209'. Cement w/ 142 sx below retainer. Pull out retainer. Spot 36 sx on top of retainer.

Set retainer @ 949'. Attempted to pump into perfs. Pressured up to 1500 psi twice with no fluid movement. Pulled out of retainer and spot 7 sx on top of retainer.

Cement from 285' to surface with 115 sx cement. Cement returns between 4 5 and 8 5/0"

Placed dry hole marker. Rehabilitate location.

14. I hereby certify that the foregoing is true and correct

Signed Ken Young Title BIA Rockdata Date 2/18/02

(This space for Federal or State official use)

Approved by [Signature] Title [Signature] Date 3/11/02

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations or to any matter within its jurisdiction.

* See instruction on Reverse Side

OPTIONAL FORM 99 (7-90)

FAX TRANSMITTAL

of pages 2

To <u>BRIAN DAVIS</u>	From <u>KEN</u>
Dept./Agency	Phone #
Fax # <u>505-761-8911</u>	Fax #
NSN 7540-01-917-7268	5099-101

GENERAL SERVICES ADMINISTRATION