

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

5. LEASE DESIGNATION

USA-NM 8222

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Double Ought

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 12 T22N R6W

12. COUNTY OR PARISH

Sandoval

13. STATE

N.M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Tesoro Petroleum Corporation

3. ADDRESS OF OPERATOR

408 First State Bank Bldg., Abilene, Texas 79604

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1695' FWL & 1045' FSL, Sec. 12 T22N R6W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7061 GL, 7074 KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL


ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7 7/8" hole to 6605'. DST #1 4000-4053 miss run. DST #2 3992-4053 Menefee Sand open 120" weak blow rec 270' oil & gas cut mud. FP 27-106#, 60" SIP 1034#. Core #1 4053-4084 Menefee Sand rec 31'; 18' sh, 6'sd NS, 7' sh. TOPS Koa 1425, Kpc 1916, Kch 3390, Kpl 4144, Kmv 4368, Kg 5237, Kgh 6148, Kgr 6208, Kd 6238, Jm 6600. Set 4 1 1/2" OD 10, 5# K-55 casing @ 5659 KB, cemented with 165 sx Pozmix "A" cement, plug down 11:30 AM 9 May 72. Opened HOWCO DV tool at 4215', circulated clean, cemented with 100 sx Pozmix "A" cement, plug down 12:30 PM 9 May 72. WOC, completion will start about 29 May 72.



RECEIVED

JUN 1 1972

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

18. I hereby certify that the foregoing is true and correct

SIGNED

Brandon H. Gray

TITLE Project Engineer

DATE 12 May 72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side