## UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side) UNITED STATES

Form approved. Budget Bureau No. 43-R1484. 5. LEASE DESIGNATION AND BURIAL NO. USA-NM 8222

GEOLOGICAL SURVEY


VICTALIS	NICTICES	AND	REPORTS	ONL	WELLC
SUNDKY	NOTICES	AND	KEPORIS	ON	WELLS

SUNDRY NOT OPEN TO SEE THE PROPERTY OF THE PRO	6. IF INDIAN, ALLOTTES OR TRUE NAME					
OH, WELL OTHER			7. UNIT AUREEMENT HA	<b>/•</b>		
NAME OF OPERATOR			8. FARM OR LEASE NAM	I I		
Tesoro Petroleum C	Double Ought					
3. ADDRESS OF OPERATOR	ADDRESS OF OPERATOR			9. WELL NO.		
408 First State Bar	1					
i. tocyrios of well (Report location clearly and in accordance with any State requirements.*  See also space 17 below.)			10. FIELD AND POOL, OR WILDCAT			
At surface			Undesig. (	Callup		
1095' FWL & 1045'	FSL, Section 12 Ta	een rew	11. SEC., T., R., M., OR B SURVEY OR AREA			
			Sec. 12 T2	22N RÓW		
14. PERMIT NO.	15. ELEVATIONS (Show whether DF,	RT, GR, etc.)	12. COUNTY OR PARISH	13. STATE		
	7074 KB		Sandoval	N. M.		
Check A	opropriate Box To Indicate N	ature of Notice, Report, or	Other Data			
NOTICE OF INTER	ITION TO:	SUBSEC	QUENT REPORT OF:			
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING W	CRUI.		

***************************************			SCROPALLY WATCHT OF				
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF		REPAIRING WELL	
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT		ALTERING CABING	
SHOOT OR ACIDIZE		ABANDON*	X	SHOOTING OR ACIDIZING		ABANDONMENT <sup>®</sup>	
REPAIR WELL		CHANGE PLANS		(Other)		· · · · · · · · · · · · · · · · · · ·	-L
(Other)				(Note: Report res Completion or Reco	ults of mu impletion F	litiple completion on We Report and Log form.)	11
ESCRETE PROPRIETA AD PO	MPLETE	n openitions (Clearly state	all pertin	ent details and give partinent de	tee includ	ling estimated data of st	

ESCRIBE PROPOSED OF COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and some pertinent to this work.) •

Preparing to plug and abandon. Plan to shoot off and pull 4-1/2" casing at 2500 approx., spot cement plugs as follows: 15 sx 5250-5400; 15 sx 4300-4450; 15 sx 3310-3460; 40 sx 1840-1990; 40 sx 1390-1540; 40 sx 170-230, 15 sx in top of surface w/standard pipe marker; also 40 sx in and out of casing stub; total 220 sx. Hole to be filled with rotary mud between plugs. Well no longer commercial, making about 1-1/2 BOPD.



SIGNED SIGNED	TITLE Project Engineer	DATE 11 Dec. 73
(This space for Federal or State office use)	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:		and Barrier (1972)

\*See Instructions on Reverse Side