

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL ☐ WELL ☐ GAS ☐ WELL ☐ OTHER ☒ Dry Hole
2. NAME OF OPERATOR
AMOCO PRODUCTION COMPANY
3. ADDRESS OF OPERATOR
501 Airport Drive, Farmington, New Mexico 87401
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
940' FWL & 1680' FSL

14. PERMIT NO. _____ 15. ELEVATIONS (Show whether DT, RT, GR, etc.)
7313' GL

5. LEASE DESIGNATION AND SERIAL NO.

Jicarilla Tribal 358

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla Tribal 358

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

Ballard Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

NW/4 SW/4 Section 5,

T-22-N, R-2-W

12. COUNTY OR PARISH

Sandoval

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE DEANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Amoco proposes to plug and abandon the above well because of lack of commercial production. The procedure will be as follows:

1. Spot a 50 sack cement plug from 2340' to PBD of 2837', squeezing 10 sacks into the perforations.
2. Spot a 10 sack cement plug from surface to 125'.
3. Cut off wellhead, erect PXA marker and clean up location.

JUL 27 1973

U.S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct.

SIGNED

Richard Hill

TITLE

Area Engineer

DATE July 26, 1973

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side