

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER		5. LEASE DESIGNATION AND SERIAL NO. Jicarilla Tribal 358	
2. NAME OF OPERATOR AMOCO PRODUCTION COMPANY		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache	
3. ADDRESS OF OPERATOR 501 Airport Drive, Farmington, New Mexico 87401		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1750' FWL & 980' FNL		8. FARM OR LEASE NAME Jicarilla Tribal 358	
14. PERMIT NO.		9. WELL NO. 8	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7269' CL est.		10. FIELD AND POOL, OR WILDCAT Ballard Pictured Cliffs EXT.	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA NE/4 NW/4 Section 8, T-22-N, R-2-W	
		12. COUNTY OR PARISH Sandoval	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:


WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) Run casing ☒	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On June 17, 1973, the 4-1/2" casing was set at 2835' with 550 sacks Class "C" cement with 50-50 Pozmix and 6Z Cel and 2 pounds Tuf Plug per sack followed with 100 sacks Class "C" Neat cement. The cement circulated.

On June 23, 1973, the 4-1/2" casing was perforated 2669-79', 2689-93', 2702-08', and 2714-19' with 1 SPF. The hole was displaced with water treated with 1X KCl and 500 gallons 15X HCl was spotted at 2719'. The well was sand-water fraced with 42,680 gallons water with 1X KCl and 10 pounds Gel per 1000 gallons. Pumped in 5,000 gallons treated water, 5,000 pounds 20-40, 20,000 pounds 10-20 and 12,500 pounds 8-12 sand. Breakdown pressure 1900, maximum treating pressure 3100, average treating pressure 2400. AIR 51 BPM.



18. I hereby certify that the foregoing is true and correct

Original Signed by
SIGNED **J. ARNOLD SWEET**


TITLE **Area Engineer**

DATE **July 6, 1973**

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____



*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
WASHINGTON, D. C.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.