Form 9-331 (May 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE.

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NM 0556258

	SUNDRY	NOTICES	AND	REPORTS ($ON\ W$	/ELLS	
οŧ	use this form f	for proposals to	drill or to	deepen or plug	back to a	different r	eservoir

Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME Gulf Federal

Sandova1

2. NAME OF OPERATOR Chace Oil Company

3. ADDRESS OF OPERATOR

313 Washington SE Albuquerque LOCATION OF WELL (Report location clearly and in accordance See also space 17 below.)
At surface Albuquerque,

Unit C 500 FNL 1800 FWL

15. BLEVATIONS (Show whether DF, RT, GR, etc.) 7022 GR

9. WELL NO. 1

10. FIELD AND POOL, OR WILDCAT Wildcat

11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA

Sec 13 T22N, R7W 12. COUNTY OR PARISH | 13. STATE

16.

14. PERMIT NO.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

Run Pipe & Cement

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS

SUBSEQUENT REPORT OF: WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL ALTERING CASING ABANDONMENT*

NM


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-28-75 Spudded

Drilled 119' of $12\frac{1}{2}$ " hole set 8-5/8" 24# csg at 116". 2-29-75 Cemented with 80 sxs of Class "A" cement

3-4-75 Reached TD of 4050'.

Ran 122 Jts. $4\frac{1}{2}$ " 10.50# csg. to 4015.25' and cemented with 3 - 5 - 75425 sxs of Halliburton Lite cement w/ 1/2# Flocele and 150 sxs Class B neat with 4% gel; and 1/4 of Flocele per sack. Full returns trace of cement at surface PBD 3999'.



at the foregoing is true and correct

TITLE President

DATE 3-7-75

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

DATE .