UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on re-

SUBMIT IN TRIPLICATE.

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

GEOLOGICAL SURVEY

NOO-C-14-20-2717 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) 7. UNIT AGREEMENT NAME WELL WELL X OTHER 2. NAME OF OPERATOR 8. FARM OR LEASE NAME FILON EXPLORATION CORPORATION Navajo 14C 3. ADDRESS OF OPERATOR C/O Minerals Management Inc. 501 Airport Dr., Suite 210, Farmington, N.M. 8
LOCATION OF WELL (Report location clearly and in accordance with any State requirements. <u>501 Airport</u> 10. FIELD AND POOL, OR WILDCAT See also space 17 below.) At surface Wildcat
11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA 330' FNL, 330' FEL, SEC. 14, T19N, R4W SEC. 14, T] 9N, R4W 12. COUNTY OF PARISH 13. STATE 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO. 6661 KB Sandoval N M16. Check Appropriate Box To Indicate Nature of Notice Report or Other Data

theat Appropriate Box to indicate Matthe of Monte, Report, of Other Bail						
NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING CASING	_
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING	ABANDONMENT*	_
REPAIR WELL		CHANGE PLANS		(Other) Run production casing X		
(Other)				(NOTE: Report results Completion or Recomple	of multiple completion on Well tion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

11-1-75

Drill 8 3/4" hole to 5662'. Ran 5347' of 7" 23# and 205' of 5 1/2" 15.5# K-55 with 5 1/2" Gearhart Owens selective completion tool. DV tool set at 2506' KB. Casing landed at 5590' KB. G.O. tools 5440'-5465' KB.

CEMENT: 1st stage-45 sx 65-35 Pozmix w/6% gel and 10# per sx Gilsonite followed by 433 sx 50-50 Pozmix w/2% gel and 10# per sx Gilsonite followed by 100 sx Class "B" cement. Plug down at 3:00AM 11-2-75. Open DV tool and circulate good cement. Circulate hole for 4 hours.

2nd stage-315 sx 65-35 Pozmix w/6% gel and 10# per sx Gilsonite followed by 50 sx Class "B" cement. Circulate good cement. Plug down 8:15AM 11-2-75

NOTE: THIS IS A TIGHT HOLE.

18. I hereby certify that the foregoing is true and correct

rea**nga**na

TITLE Mine anagement Incpate

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

DATE