Distribution:

Orig+4 (BLM); 1-Crystal; 1-Accounting; 1-Well File

Form 3160-5 (June 1990)

1. Type of Well

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1994-0135 Expires: March 31, 1993

5. Lease Designation and Serial No.

Navajo Allotted

Eagle Mesa Unit

NOO-C-14-20-2717 6. If Indian, Allottee or Tribe Name

Эι	וחנ	וזחע	AOII	CE	S WI	AD L	IEPUNI	3	OIA ME	LLO		
m	for	propo	osais	to d	drill (or to	deepen	or	reentry	to a	different	reservoir

Do not use this for Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

7. If Unit or CA. Agreement Designation

Oil Gas Well Other 2. Name of Operator	8. Well Name and No. EMU No. 3		
Merrion Oil & Gas Corporation Address and Telephone No.	9. API Well No. 30-043-20192		
610 Reilly Avenue, Farmington, NM 87401-2634 (505) 327-9801 Location of Well (Footage, Sec., T., R., M., or Survey Description)	10. Field and Pool. or Exploratory Area Eagle Mesa Entrada		
330' fnl & 330' fel Section 14, T19N, R4W	11. County or Parisn. State Sandoval County, New Mexico		
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE. RE	PORT, OR OTHER DATA		
TYPE OF SUBMISSION TYPE OF ACT	ION		
Notice of Intent Notice of In	Change of Plans New Construction Non-Routing		

MIRU Big 'A' Well Service Rig No. 16. Install 7" independent casing head and NU BOP. Received 192 jts of 2-7/8" tubing from Lybrook yard. PU 7" casing scraper and TIH on 173 joints of 2-7/8" tubing. Tag up on 7" x 5-1/2" swage at 5347' KB. TOH and LD scraper. PU Halliburton HCS 7" cement retainer and TIH on 2-7/8" tubing. Set retainer at 5329' KB. Stung out of retainer and RU

Cementers Inc. Circulated hole clean with 110 bbls of produced water. Pressure test tubing to 1200# - held OK. Sting into retainer and establish injection rate of 2.7 BPM at 100#. Spot 50 sacks (59 cu.ft.) of Class B neat cement. Displaced cement with 29 bbls of water to 5010' KB. Maximum pressure was 1000#. Sting out of retainer and reverse out 40 bbls of wate and 3 bbls of cement.

Pressure test csg to 800# for 30 mins - held OK. POH with 3 jts.

give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Finish TOH with setting tool and 2-7/8" tubing. ND BOP & remove casing head. RDMOL at 11:00 AM. 4/24/96

UED OTH		
14. I hereby terrify that the foregoing is true and correct Signed Steven S. Dunn	Tide Operations Manager	Date5/3/96
(This space for Federal or State office use) Approved by	Title	ACCEPTED FOR RECORD
Conditions of approval, if any:		MAY 1 4 1996
Title 18 U.S.C. Section 1001, makes it a crime for any person known	ngly and willfully to make to any department or agency o	f the United States any faise, fictitious or fraudulent statements

entations as to any matter within its runsdiction

