5. LEASE

UNITED	STATES	
DEPARTMENT OF	F THE IN	TERIOF
GEOLOGICA	AL SURVE	Υ

DEPARTMENT OF THE INTERIOR	NM-0559496 1 3 4 5
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	eato 8 197
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME:
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME 및 현육일 Tall Pine 중요주 등 요구의
1. oil gas X other	Tall Pine 3 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8
- Well Other	9. WELL NO. 21 22 3 bits 1 1 22 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
2. NAME OF OPERATOR	
Engineering & Production Service, Inc.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR P.O. Box 190, Farmington, NM 87401	Wildcat 11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA Sec 26, T22N, R6W
AT SURFACE: 1700' FSL & 1700' FEL	12. COUNTY OR PARISH 13. STATE 3
AT TOP PROD. INTERVAL: Same	Sandoval New Mexico
AT TOTAL DEPTH: same	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO. 19 19 19 19 19 19 19 19 19 19 19 19 19
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
DECUSAT FOR ADDROLLA TO	7170 GL, 7183 DF 등 등원들로
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	7,8% 3 7 6444
TEST WATER SHUT-OFF	Figure 10 to 40 to
SHOOT OR ACIDIZE	To top Visited
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)- 글 뜻 글 불
MULTIPLE COMPLETE	ettoiland bottengo besteering service to the tool and method or the tool and the to
ABANDON*	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen	irectionally drilled, give subsurface locations and to this work.)*
The subject well has been thoroughly tested and proprose to plug the well as follows:	roven to be non-commercial. We
spot cement plug 2200'-2	2000' ଶ୍ରିଶ୍ରିଟି 😸 ବ୍ୟିକ୍ରି
spot cement plug 1675'-1	1575' 원강성경우 원 생활일실
Perforate at 175' and pump 25 sacks cement to tie	into surface pipe at 142
Spot 10 sack: cement plug at surface. Place marke	er. Goden Handel
Surface will be returned to condition required by	and Augustican managed partial well as the standard partial as the standard partial and the stan
	A CONTRACTOR OF THE STATE OF TH
	ilimdi A Li Sa Se Ci Se Se Ci Se Ci Se Ci Se Ci Se Ci Se Ci Se Ci Se Se Ci Se Se Ci Se Se Ci Se Se Ci Se Se S
	ा १ के <b>र्विक्ति है</b> है <b>है है है</b>
	#70 g (1 <b>2</b> 1 <b>5</b> 5 5 5 <b>5 4</b> 1
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	7 2 3 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
SIGNED JULIA QUELLA TITLE Agent	DATE 1-4-78 2 2 2 2
This space for Federal or State office	ce use) ନୁର୍ଦ୍ଧ ନୁଷ୍ଟ ନୁଷ୍ଟ ଅନ୍ତର୍ଶ କଥା । ଜଣ ଜଣ ଅନ୍ତର୍ଶ କଥା କଥା । ଜଣ ଜଣ ଅନ୍ତର୍ଶ କଥା । ଜଣ
APPROVED BY TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	
4	jaga <b>jan 129978</b>
. A	· · · · · · · · · · · · · · · · · · ·

\*See Instructions on Reverse Side

