٠ī

14. PERMIT NO.

16

UNITED STATES DEPARTMENT OF THE INTERIOR (Other instructions on verse side)

SUBMIT IN TRIPLICATES

Form approved. Budget Bureau No. 42-R1424 5. LEASE DESIGNATION AND SERIAL NO.

LOGICAL SURVEY	NM-0556258
	6. IF INDIAN, ALLOTTER OR TRIBE NAME

	5	UN	יאטו	1	NOII	CF2	ΑI	ND	REF	УCR	115	ON	M	/ELLS	
ю п	t use	this	torm Use	for "Al	proposa PPLICA	lls to TION	drill FOR	or t PE	o deep RMIT—	en or " for	plug such	back propo	to a sals.)	different	reservoir.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

OTHER 2. NAME OF OPERATOR Chace Oil Company, Inc. ADDRESS OF OPERATOR

Gulf Federal 9. WELL NO.

313 Washington S.E., Albuquerque, N. Mex. 871
LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface N. Mex. 87108

3 10. FIELD AND POOL, OR WILDCAT

Unit "G" 1650' NL & 1955' EL

Rusty Menefee 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 13 T22N R7W

7020' GR

15. ELEVATIONS (Show whether DF, RT/GR, etc.)

Sandova L N.Mex.

Check Appropriate Box To Indicate Natura of Notice, Report, or Other Data NOTICE OF INTENTION TO:

SUBSEQUENT EXPORT OF:

(Other) Progress Report

CEST WATER SHUT-OFF PULL OR ALTER CASING SHOOT OR ACIDIZE ABANDON*

FRACTURE TREATMENT X SHOOTING OR ACIDIZING X ALTERING CASING

CEPAIR WELL CHANGE PLANS Other

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-16-76 Spudded with Coleman Rig #3 at 3:00 PM drilled 70' surface hole and set 63' of 24# 8-5/8" Csg., and cemented with 85 sxs of class B cement with 2% CC. Plug down at 7:00 PM.

2-17-76 7:00 AM was drilling at 701' Roads very muddy. Reached TD of 2004' 11:00Pl 2-18-76 Logged induction and density logs out at 6:00PM. 51 Jt's of $4\frac{1}{2}$ 10.50 lbs, set at 2040 KB, float 2018 KB, basket @ 1855-1450 & 1540. Centralizer 2018, 1950, 1850, 1540, cemented with 355 sxs class B 50/50 posmix with 4% jell & 2% CC pailed in 100 sxs class B 4% jell & 2% CC. Plug down 3:45 AM pressured up on float at 1500 ft. did not hold, holding pressure for six hours.

2-23-76 Perforated 1963-1980, 1955-1958, 1952-1954 and 1943-1949 with 3 1/8" ballset 1 shot per foot. Broke down formation. Breakdown pressure 2100# Instant shut in 450#.

2-24-76 Frac'd well with 60,000 # 10-20 sand and 40,000. gal of slick water. Treating pressure min 1900# max 3150# avg 2500# Rate of inj. 45 Bbls. per minute. Dropped 9 balls in 6 stages. Sand water ratio was 13# sand to gallon of water. Instant shut in pressure 650# after 15 min. 550# Shut in overnight.

18. I hereby certify that the foregoing is true a	nd correct		
IN. I hereby certify that the foregoing is true a	TITLE President	DATE	2-25-76
(This space for Federal or State office use)	Û		
APPROVED BY	TITLE	DATE	
CONDITIONS OF APPROVAL, IF ANY:			