

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR  
Chace Oil Company, Inc.

3. ADDRESS OF OPERATOR  
313 Washington, SE, Albuquerque, NM 87108

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: Unit 'F', 1650' FNL & 1850' FWL  
AT TOP PROD. INTERVAL: SAME  
AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON* (other)	<input checked="" type="checkbox"/>	<input type="checkbox"/>

5. LEASE  
N00-C-14205361

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Rusty Navajo

9. WELL NO.  
4

10. FIELD OR WILDCAT NAME  
Rusty Chacra

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 26, T22N, R7W

12. COUNTY OR PARISH  
Sandoval

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6773' KB

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

JAN 30 1985

BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The following plugging information was obtained from Jim Lovato of your office 1/28/85:

Plugging operations to begin in February, 1985.

Set a cement plug from 1465'-1731' to cover the Chacra Interval.

Set a 100' cement plug from 1082'-1182' to cover the Pictured Cliffs tops.

Set a 100' cement plug from 868'-968' to cover the Fruitland tops.

Set a 100' cement plug from 522'-622' to cover the Ojo Alamo tops.

Set a 100' cement plug from surface to 100'.

Set a dry hole marker.

Blade and reseed location.

RECEIVED

FEB 06 1985

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_ TITLE President

OIL CON. DIV. APPROVED  
DIST. 3

DATE 1/29/85

(This space for Federal or State office use)

APPROVED BY *B.W. Mills* TITLE \_\_\_\_\_

DATE FEB 01 1985

CONDITIONS OF APPROVAL, IF ANY:

*for M. Milendash*  
AREA MANAGER

\*See Instructions on Reverse Side

NMOCC

BUREAU OF LAND MANAGEMENT  
Caller Service 4104  
Farmington, New Mexico 87499

Attachment to Notice of  
Intention to Abandon

Re: Permanent Abandonment

Well: 4 Rusty Navaho

CONDITIONS OF APPROVAL

1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal Leases."
2. The Farmington office (telephone (505) 325-4572) is to be notified in sufficient time for a representative to witness all plugging operations.
3. Blowout prevention equipment is required.
4. In addition to normal filling of pits and cleanup of location, additional surface restoration work may be required, i.e. ripping of pad and/or access road, reseeding, etc. We have asked the Surface Management Agency for the surface restoration requirements for this well and we should be able to furnish you these requirements within 30 days. After plugging the well and before making final clean-up, you should contact this office unless you have already been advised as to what additional surface restoration work is required.
5. The following modifications to your plugging program are to be made (when applicable):

You are further advised that any instructions, orders or decisions issued by the Bureau of Land Management are subject to technical and procedural review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4 and 43 CFR 4.700.

Office Hours: 7:45 A.M. to 4:30 P.M.

GENERAL REQUIREMENTS FOR  
PERMANENT ABANDONMENT OF WELLS ON FEDERAL LEASES  
FARMINGTON RESOURCE AREA

1. Secure prior approval before changing the approved plugging program.
2. Plugging equipment used shall have separate mixing and displacement pumps and a calibrated tank to assure proper displacement of plugs.
3. A proper tank or pit will be used to contain all fluids pumped from the well during plugging operations.
4. All cement plugs are to be placed through tubing (or drillpipe) and shall be a minimum of 15 sacks or 100 feet in length, whichever is greater.
5. Any cement plug placed when well is not full of fluid, or when well may be taking fluid, will be touched after cement has set to verify proper location.
6. Mud must be placed between plugs. Minimum consistency of plugging mud must be 9.2 lbs/gal. Brine is to be utilized for mixing mud where possible.
7. Within 30 days after plugging work is completed, file Subsequent Report of Abandonment, Form 3160-5 (formerly 9-331), in quintuplicate with Area Manager, Bureau of Land Management, Caller Service 4104, Farmington, New Mexico 87499. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.
8. All permanently abandoned wells are to be marked with a permanent monument, on which has been stenciled or beaded the well name, well number, and well location by quarter-quarter, section, township and range. The monument is to be of steel pipe, not less than four inches in diameter, cemented permanently in the ground, and extending four feet above general ground level. The top should be closed with a screw cap, welding, or a cement plug.
9. After plugging work is completed:
  - a. Fill all pits, rat hole and cellar.
  - b. Clean well location of all equipment, concrete bases, pipe, junk and
  - c. Cut or remove tie downs.
  - d. If last well on lease, and no additional drilling is contemplated, fill tank battery pits, remove battery equipment, and clean and level battery location.
  - e. Accomplish surface restoration as specified by the surface management agency or land owner.

All above are minimum requirements. The Subsequent Report of Abandonment will not be approved and the period of liability under the bond of record terminated until the lease is inspected and surface work approved.

Please advise this office when the well location is ready for final inspection.

You are further advised that any instructions, orders or decisions issued by the Bureau of Land Management are subject to technical and procedural review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4 and 43 CFR 4.700.