

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> <u>Dry Hole</u>		5. LEASE DESIGNATION AND SERIAL NO. <u>365</u>
2. NAME OF OPERATOR <u>Universal Resources Corporation</u>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME <u>Jicarilla Apache</u>
3. ADDRESS OF OPERATOR <u>910 Nat'l Foundation W. Bldg., 3555 NW 58 Okla. City, Okla. 73112</u>		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <u>1660' FSL & 1010' FWL (NW SW) Sect. 28-22N-2W</u>		8. FARM OR LEASE NAME <u>Jicarilla 28</u>
14. PERMIT NO. <u>TR-NM(A)-77-1</u>		9. WELL NO. <u>1</u>
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <u>GR 7438 RKB 7452.5'</u>		10. FIELD AND POOL, OR WILDCAT <u>W/C</u>
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>Sect. 28-22N-2W</u>
		12. COUNTY OR PARISH <u>Sandoval</u>
		13. STATE <u>New Mexico</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well 11-9-76 and set 8-5/8" surface casing @ 299' and cemented w/250 sacks cement. Cored well from 7053 - 7113' and recovered 60' total. 22' blk sh, 38' SS light gray, fine grain, hard sh, stain, no fluor., gas odor on new break, few fractures, shaly in bottom. Total depth 7320'. No Drill stems were taken. Well dry and abandoned.

PROPOSED PLUG SETTING DEPTHS

Plug #1	7030-7130	35 sacks cement (Dakota)
Plug #2	5050-5150	35 sacks cement (Mancos Shale)
Plug #3	4250-4400	50 sacks cement (Mesaverde)
Plug #4	2675-2775	35 sacks cement (Pictured Cliff)
Plug #5	2140-2290	50 sacks cement (Ojo Alamo)
Plug #6	275-325	20 sacks cement (half in & half out of surf)
Plug #7	0 - 30	10 sacks cement w/ marker to be installed.

18. I hereby certify that the foregoing is true and correct

SIGNED

D. N. Baker

TITLE

Agent

DATE

12-1-76

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side DEC 7 1976