Form 9-330
(Rev. 5-68)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE* (See other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

5. LEASE DESIGNATION AND SERIAL NO.: JICARILLA 15

6. IF INDIAN, ALLOTTEE OR TRIBE NAME: JICARILLA APACHE

7. UNIT AGREEMENT NAME:

8. FARM OR LEASE NAME: CHACE APACHE 15

9. WELL NO.: 1

10. FIELD AND POOL, OR WILDCAT: CHACON DAKOTA

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA: Sec. 20 T23N-R3W

12. COUNTY OR PARISH: Sandoval

13. STATE: NM

1a. TYPE OF WELL: OIL WELL [X] GAS WELL [ ] DRY [ ] Other

b. TYPE OF COMPLETION: NEW WELL [X] WORK OVER [ ] DEEP-EN [ ] PLUG BACK [ ] DIFF. RESVR. [ ] Other

2. NAME OF OPERATOR: Chace Oil Company, Inc.

3. ADDRESS OF OPERATOR: 313 Washington, SE, Albuquerque, NM 87108

4. LOCATION OF WELL (*Report location clearly and in accordance with any State requirements*)*
At surface: Unit "A" 790' NL & 790' EL
At top prod. interval reported below: Same
At total depth: Same

14. PERMIT NO.: DATE ISSUED:

15. DATE SPUDDED	16. DATE T.D. REACHED	17. DATE COMPL. (*Ready to prod.*)	18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*	19. ELEV. CASINGHEAD
2-27-77	3-13-77	3-29-77	7224'GR 7237 DF	7226'

20. TOTAL DEPTH, MD & TVD	21. PLUG, BACK T.D., MD & TVD	22. IF MULTIPLE COMPL., HOW MANY*	23. INTERVALS DRILLED BY	ROTARY TOOLS	CABLE TOOLS
7650	7620'		→	All	

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*
7237' - 7265'
7348' - 7362'

25. WAS DIRECTIONAL SURVEY MADE: Yes

26. TYPE ELECTRIC AND OTHER LOGS RUN: Induction & Density Logs

27. WAS WELL CORED: No

28. CASING RECORD (*Report all strings set in well*)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
10 3/4"	28	200	13½"	160 sxs	none
4 ½"	10.5	7660	7 7/8"	1000 sxs	none

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2 3/8	7340'	none

31. PERFORATION RECORD (*Interval, size and number*)
7237-65' 1 shot per foot 3 1/4"
7348-62' 2 shot per foot 3 1/4"

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
7237-65	Frac'd w/120,000# 20-40sd. w/slick water 111,000 gals
7348-62	Frac'd w/80,000 #20-40sd. & 80,000 gals slick water

33.* PRODUCTION

DATE FIRST PRODUCTION	PRODUCTION METHOD (*Flowing, gas lift, pumping—size and type of pump*)	WELL STATUS (*Producing or shut-in*)
4-10-77	flowing	shut in WOPL

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD →	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
5-19-77	3 days	17/64	→	189	690	0	3650

FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE →	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)
200#	820#	→	63	230	0	46

34. DISPOSITION OF GAS (*Sold, used for fuel, vented, etc.*): vented

TEST WITNESSED BY: Red Walsh

RECEIVED JUN 2 1977 OIL CON. COM. DIST. 3

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Royce McCarty TITLE President DATE 5-28-77

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.
If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.
Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.
Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.
Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.
Item 29: *"Sacks Cement":* Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.
Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
Pictured cliffs	3020	3120	sandy-shale-gas
Cliff House	4560	4650	sand-hard & tight
Pt. Lookout	5120	5210	Shaley sand with coal strs.
Gallup	6100	6700	Shaley sand tight- show of gas
Greenhorn	7150	7215	Hd. tight limey sand
Dakota A	7233	7280	Sand-tight oil & Gas
Dakota B	7340	7365	Sand-tight oil & gas
Dakota D	7432	7460	Sand hd.-tight-water

38. GEOLOGIC MARKERS

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH
Same as porous zones		

U.S. GOVERNMENT PRINTING OFFICE: 1969—O-883636