UNITED STATES DEPARTMENT OF THE INTERIOR

	Form Approved. Budget Bureau No. 42–R1424
	5. LEASE
	NM-7766 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
nt	7. UNIT AGREEMENT NAME
	8. FARM OR LEASE NAME Federal 7-27
	9. WELL NO. 7-27
	10. FIELD OR WILDCAT NAME Wildcat Mesaverde
7	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 27, T19N, R3W
	12. COUNTY OR PARISH 13. STATE Sandoval NM
 <u>=</u> ,	14. API NO.
	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6740 RKB, 6727 GR
	(NOTE: Report results of multiple completion or zone change on Form 9–330.)

Del Milliant Of the Internot	MM-1100				
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME				
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME				
1. oil gas well other	Federal 7-27				
2. NAME OF OPERATOR	9. WELL NO. 7-27				
Petro Lewis Corporation 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Wildcat Mesaverde				
P. O. Box 937, Levelland, Texas 79336 4. DOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 27, T19N,R3W				
AT SURFACE: 2210' FNL, 2065' FEL, Sec. 27, AT TOP PROD. INTERVAL: Same T-19N, R3W AT TOTAL DEPTH: Same	12. COUNTY OR PARISH 13. STATE Sandoval NM 14. API NO.				
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)				
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone change on Form 9–330.)				

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Jan. 4, 1978 - GIH w/60 jts 2 7/8" tbg to TD 1850.70'. Spotted cement plug from TD 1850' to 1696.05'. Spotted 14 bbls mud from 1696' to 1350'. Spot cement plug 1350' to 1210'. Spot mud 1210' to 63'. Cement plug from surface to 63'. PAA Marker Installed.



Subsurface Safety Valve: Manu. and Type		300		Set	@	
			A PARTY OF THE PROPERTY OF STREET		-	
18. I hereby certify that the foregoing is true and correct						
SIGNED GROUNDEN TITLE	Dist.	Admin.	DATE	February	27.	1980

This space for Federal or State office use)

FOR JAMES F. SIMS

APPROVED BY

CONDITIONS OF APPROVAD LITTARY

hstructions on Reverse Side