

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> <i>Plug and Abandonment</i>		5. LEASE DESIGNATION AND SERIAL NO. <i>NM-A 27870</i>	
2. NAME OF OPERATOR <i>Houston Oil &amp; Minerals Corporation</i>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME -	
3. ADDRESS OF OPERATOR <i>1700 Broadway, Suite 504, Denver, Colorado 80290</i>		7. UNIT AGREEMENT NAME -	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <i>990' FNL, 990' FEL, Sec. 1, T15N, R4W</i>		8. FARM OR LEASE NAME <i>Booth Drought</i>	
14. PERMIT NO.		9. WELL NO. <i>2</i>	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <i>6195' (GR)</i>		10. FIELD AND POOL, OR WILDCAT <i>Wildcat</i>	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <i>Sec. 1, T15N, R4W</i>	
		12. COUNTY OR PARISH <i>Sandoval</i>	13. STATE <i>N.M.</i>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Plugged well as follows (Class "B" cement, utilizing 9.1 lb/gal low solids/non-dispersed mud):

- #1: 6800'-6550' (89 sx.)
- #2: 4900'-4700' (73 sx.)
- #3: 4300'-3800' (173 sx.)
- #4: 2800'-2400' (143 sx.)
- #5: 1700'-1550' (54 sx.)

NOTE: Hole stood full after displacing each plug.

Set 10 sk. plug at surface and installed dry hole marker.



18. I hereby certify that the foregoing is true and correct

SIGNED

*Ronald D. Scott*  
Ronald D. Scott

TITLE *Division Drilling Engineer*

DATE *April 13, 1977*

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: