Form	9-331
(Mav	1963)

1.

## UNITED STATES DEPARTMENT OF THE INTERIOR verse

SUBMIT	IN	TRIPL	ICA'	, 10 a
(Other i	nstr	uctions	on	re-
verse side	a)			

Form approved. Budget Bureau No. 42-R1424. 5, LEASE DESIGNATION AND SERIAL NO.

NM	2	6	6	5	5

SUNDRY	NOTICES	AND	<b>REPORTS</b>	ON	WELLS	
--------	---------	-----	----------------	----	-------	--

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.)

GEOLOGICAL SURVEY

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A

PLR,

9. WELL NO.

- 1	7. UNIT	AGREE	MENT	NΔ
- 1	/-			
ı	N/Z	4	**	

8. FARM OR LEASE NAME

WELL X GAS WELL 2. NAME OF OPERATOR

Rijan Oil Company, Inc.

3. ADDRESS OF OPERATOR

OTHER

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.)

At surface 20 First Plaza, Suite 402, Alb. NM

Inc

10. FIELD AND POOL, OR WILDCAT

Media Gallup 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 23 T19N,R3W NMPM

760' fwl, 1650' fs/l

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6764' GR, 6768' KB

12. COUNTY OR PARISH | 13. STATE

Sandoval

New Mexico

14. PERMIT NO.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PULL OR ALTER CASING MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS REPAIR WELL Complete Menefee

WATER SHUT-OF

PRACTURE TREATMENT

SHOOTING OR ACIDIZING

REPAIRING WELL ALTERING CASING

ABANDON MENT

(Note: Report results Completion or Recomp Doubtiple completion on Well tion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical nent to this work.) • ncluding estimated date of starting any depths to all markers and sones perti-

Plan to P&A Gallup and perforate Menefee formation. w/375 sx. 50/50.

52" set @3250 \

Gallup perforations: 2696 -2708, 2716 -2724, 2890 -2896, 2984 -2990, 3034 -3040, 3044 -3048, 3118 -3124, 3146 -3160 and 3172 -3178 .

Plan to:

- Plug Gallup formatic/with sufficient cement to bring l. top of cement 100 above top of perforations,
- 2. Run cement bond log to locate top of cement,
- 3, Set CIBP at approximately 1800 %.
- Perforate with 4 holes above BP and bring cement approximately 300 above Menefee formation.
- Perforate Menefee from 1668'-1678' with 2 SPF.
- Wash perforations with mud acid and swab back.
- If results favorable, put Menefee on production; if not, P&A well,

18. I hereby certif

SIGNED

TITLE Petroleum Engineer

DATE .

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

ah 3m

\*See Instructions on Reverse Side

NMOCC

DISTRICT OIL & GAS SUPERVISOR