

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other
- 
2. NAME OF OPERATOR  
Chace Oil Company, Inc.
- 
3. ADDRESS OF OPERATOR  
313 Washington, SE, Albuquerque, NM 87108
- 
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: Unit 'M' - 790' FSL & 1150' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,  
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- |                      |                                     |
|----------------------|-------------------------------------|
| TEST WATER SHUT-OFF  | <input type="checkbox"/>            |
| FRACTURE TREAT       | <input type="checkbox"/>            |
| SHOOT OR ACIDIZE     | <input type="checkbox"/>            |
| REPAIR WELL          | <input type="checkbox"/>            |
| PULL OR ALTER CASING | <input type="checkbox"/>            |
| MULTIPLE COMPLETE    | <input type="checkbox"/>            |
| CHANGE ZONES         | <input type="checkbox"/>            |
| ABANDON*             | <input checked="" type="checkbox"/> |
| (other)              |                                     |

## SUBSEQUENT REPORT OF:

- |  |
|--|
|  |
|  |
|  |
|  |
|  |
|  |
|  |

RECEIVED

AUG 17 1933  
 (NO

U. S. GOVERNMENT  
PRINTING OFFICE

(NOTE: Report results of multiple completion or zone change on Form 9-1330.)

0.) AUG 26 1983

OIL CON. DIV.  
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plugging operations to begin the week of August 22, 1983.  
Move in workover rig. Squeeze cement perforations from 1564'-1812'  
with 50 sks. Class B neat (59 CF) cement. Set a cement  
plug from a depth of 50' to surface. Set marker in cement.  
Blade location. *Khab.*

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. A. Miller TITLE President DATE August 15, 1983

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_ **APPROVED**  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_

APPROVED  
AS AMENDED

AUG 12 1983

M. MILLENBACH  
AREA MANAGER

**\*See Instructions on Reverse Side**

**NMOCC**