

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-6680

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo 21

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Rusty Chacra Extension

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Section 21-T22N-R7W

12. COUNTY OR PARISH 13. STATE

Sandoval

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL ☐ GAS ☒ OTHER  
WELL WELL

2. NAME OF OPERATOR

Dome Petroleum Corp. - Benson Mineral Group, Inc. (Agent)

3. ADDRESS OF OPERATOR

Benson Mineral Group, Inc. 3200 Anaconda Tower, 555 17th Street  
Denver, Colorado 802024. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1040' FNL &amp; 1190' FEL, Section 21-T22N-R7W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6802 GR

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other) Set casing


REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

5-30-78: Spud 20:30. Drill 8 3/4" hole. Drl to 116'.

5-31-78: Ran 116' of 7", 20 lb casing. Set casing at 116' with 50 sacks of  
cement. Good circulation cement. Pressure test casing to 600 psi.

6-1-78: Drilling at 989'.

6-2-78: Drilling at 1555'.

6-3-78 thru 6-5-78: TD 1882'. Ran logs. Ran 1869' of 4 1/2", 9.5 lb casing. Set  
casing at 1879' with 230 sacks of 50-50 Poz, 6% gel, 1/4 lb flow seal/sack,  
followed with 50 sacks class "B" neat. Rig released at 03:00 6-5-78.

18. I hereby certify that the foregoing is true and correct

SIGNED

Paul C. Ellison

TITLE Production Manager

DATE June 5, 1978

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

DATE

JUN 7 1978

\*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.