					/	
Form 9-331	1	UNITED STATES SUBMIT IN TRIPLICATE.			Form approved	
(May 1983)		ARTMENT OF THE INTERIOR (Other Instructions on re-		Budget Bureau/No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.		
	GEOLOGICAL SURVEY			NM 9782 /		
SUNDRY NOTICES AND REPORTS ON WELLS				6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
(Do not use	UNDRY NOT this form for propose Use "APPLICA	ICES AND REPORTS Calls to drill or to deepen or plug by ATION FOR PERMIT—" for such pr	ON WELLS ack to a different reservoir. oposals.)			
1.		7. UNIT AGREEMENT NAME				
OIL GA	S OTHER					
2. NAME OF OPERAT		8. FARM OR LEASE NAME				
Dome Petroleum Corporation				Federal 24-21-6		
3. ADDRESS OF OPERATOR & Minerals Management Inc., Suite 105,				9. WELL NO.		
501 Airport Drive, Farmington, New Mexico 87401 4. Location of Well (Report location clearly and in accordance with any State requirements.*				10. FIELD AND POOL, OR WILDCAT		
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface						
				Wildcat 11. SEC., T., R., M., OR BLK. AND		
		-		SEC. 24, T2		
330' FSL, 2310' FWL, SEC. 24, T21N, R6W				NMPM		
14. PERMIT NO.	2310 1441	15. ELEVATIONS (Show whether DF,	RT, GR, etc.)	12. COUNTY OR PARISH	13. STATE	
		6917' GL, 6929	9' KB	Sandoval	N.M.	
16.	Charle A =			Other Data		
Clieck Appropriate Box to malcule realists of resolution of				GENT REPORT OF:		
NOTICE OF INTENTION TO:				T T REPORT OF:		
TEST WATER SHUT-OFF PULL OR ALTER CASING			WATER SHUT-OFF	REPAIRING WELL		
FRACTURE TREA	T .	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CA		
SHOOT OR ACIDE		ABANDON*	(Other) Spud & Se	ABANDONMEN		
(Note: Report results				of multiple completion on Well		
(Other)	ED OB COMPLETED OPE	RATIONS (Clearly state all pertinent	t details and give pertinent dates	pletion Report and Log for s. including estimated date	e of starting any	
proposed work nent to this we	k. If well is directio	onally drilled, give subsurface location	ions and measured and true vertice	cal depths for all markers	and zones perti-	
12-12-77	Spudded 13	3 1/4" hole at 8:	15 p.m. Ran 5 it	s (185') 9 5	/8",	
12 12 .,	36#. K-55	3 1/4" hole at 8:1 , ST&C casing set	at 196' KB with	200 sx Class	"B"	
	cement, 29	& CaCl. Plug down	n at 12:01 a.m.,	12-13-77. C:	irculated	
	cement.	2	·			
		·				
		CONF	IDENTIAL			
		COLAT		S. S		
				The state of the s		