

WELL NAME: Boling Federal #8-22 FIELD: S.W. Media DATE: 12/19/77

AFE NO: _____ ELEV.: _____ GRD: _____ KB: _____ PROPOSED TD: 5425'

LOCATION (SURF.): 990' FNL & 2160 ²¹⁶⁰ FWL OF SEC.: 22 T 19N R 3W

COUNTY: Sandoval STATE: New Mexico SPACING: _____

LOCATION (BOTTOM HOLE): _____

GEOLOGICAL ESTIMATES

<u>ZONE</u>	<u>TOP</u>	<u>THICKNESS</u>	<u>CONTENT</u>	<u>ZONE</u>	<u>TOP</u>	<u>THICKNESS</u>	<u>CONTENT</u>
<u>Menefee</u>	<u>1200'</u>	_____	_____	_____	_____	_____	_____
<u>Gallup</u>	<u>2900'</u>	_____	_____	_____	_____	_____	_____
<u>Entrada</u>	<u>5325'</u>	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____

<u>CORING NO.</u>	<u>TYPE</u>	<u>HORIZON</u>	<u>INTERVAL FROM-TO</u>	<u>FOOTAGE</u>	<u>REMARKS</u>
<u>Schlumberger</u>	<u>SWC</u>	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

DRILL STEM TESTS

WATER SHUT OFF TESTS

<u>NUMBER</u>	<u>HORIZON</u>	<u>NUMBER</u>	<u>HORIZON</u>	<u>NUMBER</u>	<u>HORIZON</u>	<u>NUMBER</u>	<u>HORIZON</u>
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____

WELL SURVEYS (list types by code numbers as follows: directional and/or deviation (1), deflection (2), caliper (3), temperature (4), electrical (5), radioactive (6), geograph (7), photoclinometer (8), mudlogging (9), and other (10) and name of that type).

<u>DEPTH POINTS</u>	<u>TYPE</u>	<u>HOLE SIZE</u>	<u>REMARKS</u>
<u>0-TD</u>	<u>(7) Geograph</u>	<u>14 3/4 & 9 7/8</u>	_____
<u>0-TD</u>	<u>(2) Deflection</u>	<u>14 3/4 & 9 7/8</u>	<u>one every 500'</u>
<u>500-TD</u>	<u>(6) GR-CNL-FDC</u>	<u>9 7/8</u>	_____
<u>500-TD</u>	<u>(5) DIL</u>	<u>9 7/8</u>	_____
<u>0-2900</u>	<u>(4) Temperature</u>	<u>Inside Casing</u>	<u>locate TOC</u>
<u>2000-TD</u>	<u>(10) CBL-VDL</u>	<u>Inside Casing</u>	<u>Cmt. bond log w/GR-collor for perf.</u>