

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 6676

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Dome Petroleum Corp. - Benson Mineral Group, Inc. (Agent)

3. ADDRESS OF OPERATOR  
Benson Mineral Group, Inc., 3200 Anaconda Tower  
555 17th Street, Denver, Colorado 80202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

820' FNL, 1520' FEL, Sec 30-T22N-R6W

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Dome Rusty 30-22-6

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Rusty Chacra Extension

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 30-T22N-R6W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6922' GR

12. COUNTY OR PARISH

Sandoval

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set Casing

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5-25-78: Spud. Drilling at 110', Ran 98' of 7" casing, circ cmt. Pressure tst to 600 psi.  
5-26-78 thru 5-29-78: Total depth 2093'. Wellex on location to log. Log TD 2093'.  
Ran 2082' of 4½" casing to 2093'. Cemented with 240 sacks of 50-50  
poz, 6% gel, ¼ pound celloflake/sack, followed with 50 sacks of Class "B"  
neat. Circ good cement. Plug down and rig released at 21:00 5-29-78.



18. I hereby certify that the foregoing is true and correct

SIGNED

Paul C. Ellison

TITLE Production Manager

DATE 5-30-78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

RECEIVED

MAY 31 1978

\*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY  
DENVER, COLO.