UNITED STATES

DEPARTMENT OF THE INTERIOR (Other Instructions on

Form approved. Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND BERIAL NO.

GEOLOGICAL SURVEY					NM-6678		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)					6. If INDIAN, ALLOTTE.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
1.	OIL GAS WELL OTHER				7. UNIT AGREEMENT NA	ME	
2.	Odessa Natural Corporation Att: John Strojek				8. FIRM OR LEASE NAME DOME etal Federal 28		
3.	. ADDRESS OF OPERATOR				9. WELL NO.	9. WELL NO.	
	P. O. Box 3908, Odessa, Texas 79760				1	1	
4.	LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface				10. FIELD AND POOL, OR WILDCAT Wildcat		
	1800' FSL, 840'FEL				SURVEY OR AREA	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 28-T23N-R6W N.M.P.M.	
14.	. PERMIT NO.	15. ELEVATIONS (Show w	IONS (Show whether DF, RT, GR, etc.)		12. COUNTY OR PARISH	13. STATE	
		72 ⁰ 6' G	R		Sandoval	N.M.	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF REPAIRING WELL FRACTURE TREAT MULTIPLE COMPLETE ALTERING CARING FRACTURE TREATMENT SHOOT OR ACIDIZE ABANDON* ABANDONMENT* SHOOTING OR ACIDIZING REPAIR WELL CHANGE PLANS (Other) (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) proposed work. Is nent to this work.)


4-16-78 Spud well 4-18-78 T.D. 137'

16.

Ran 3 jts. 8 5/8", 24.0 lb., K-55 casing (134.80) Set at 134.80'with 100 sacks Class "B" cement with 3% Calcium chloride and ¼ lb. Flocele per sack. Cement circulated. Pressure test with 500 psig. Test O.K.

5-16-78 T. D. 2838'

Ran 64 jts. 4½", 10.50 lb., K-55 Casing (2816.92) set at 2830' with: 125 sacks, 50/50 Pozmix with 6 lbs. salt & 64 lbs. Gilsonite per sack.



U. S. STORROGEL SURVEY Districted, Octo.