

Robert Ramirez

Form 9-331
(May 1965)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved
Budget Bureau No. 40-R1424
5. LEASE DESIGNATION AND SERIAL NO.
NM-16586

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a well. Use "APPLICATION FOR PERMIT" for such purposes.)

RECEIVED
MAR 11 1983

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	6. IF INDIAN, AGENCY OR TRIBAL NAME
2. NAME OF OPERATOR BCO, Inc.	7. UNIT AGREEMENT NAME
3. ADDRESS OF OPERATOR P. O. Box 669 Santa Fe, New Mexico 87501	8. FARM OR LEASE NAME Federal I
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1850' FNL 1700' FEL Sec. 33 T23N R7W	9. WELL NO. 1
14. PERMIT NO.	10. FIELD AND FORM. OR WILDCAT Undesignated Gallup
15. ELEVATIONS (Show whether DF, RT, CR, etc.) GR 6888	11. SEC., T., R., OR BLK. AND SURVEY OR AREA Sec. 33 T23N R7W
	12. COUNTY OR PARISH Sandoval
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	WELL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT ☐
REPAIR WELL ☒	CHANGE PLANS ☐	(Other) ☐	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and pertinent to this work.)

Believe well has casing failure. Intend to set RBP above Gallup perfs (4928-5144) and then use a packer to find the hole in the casing. Intend to repair said hole with cement, let cement set for at least 72 hours, then drill out cement, remove RBP, swab well and place back in production.

RECEIVED
MAR 11 1983
OFFICE OF THE DISTRICT ENGINEER

18. I hereby certify that the foregoing is true and correct

SIGNED Wm Bar TITLE Office Manager DATE 3/10/83

(This space for Federal or State office use)

APPROVED BY James F. Sims TITLE DISTRICT ENGINEER DATE 3/10/83

CONDITIONS OF APPROVAL IS h2