| 5 BL Form 3160 (November (Formerly | –5 ¹⁹⁸³⁾ 9–331) DEPARTM | HLB; 1 DS - 7 cop INITED STATES ENT OF THE INTER I OF LAND MANAGEMEN | SUBMIT IN TRIPLIC (Other instructions of Verse aide) | EATE® Expires August 31, 1985 |
|---|--|---|--|---|
| (De | SUNDRY NOTIC | CES AND REPORTS Is to drill or to deepen or plus ITON FOR PERMIT—" for such | ON WELLS | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| 1. 4 | | | | 7. UNIT AGREEMBNT NAME |
| OIL X GAB OTHER 2. NAME OF OPERATOR | | | | S. FARM OR LEASE NAME |
| BCO, Inc. | | | | Federal B · |
| 3. ADDRESS OF OPERATOR 135 Grant, Santa Fe, New Mexico 87501 | | | | 9. WELL NO. |
| 4. Location of Well (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface | | | | Alamito Gallup |
| 860' FNL and 790' FWL Sec 34 T23N R7W | | | | Sec 34 T23N-R7W |
| 14. PERMIT | NO. | 15. ELEVATIONS (Show whether 6911'. GR | of, RT, GR, etc.) | Sandoval · NM · |
| 16. | Check App | propriate Box To Indicate | Nature of Notice, Report | , or Other Data |
| PRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other) | | ULTIPLE COMPLETE BANDON® HANGE PLANS | WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZIN (Other) (Note: Report Completion or F | results of multiple completion on Well ecompletion Report and Log form.) |
| prope | E PROPOSED OR COMPLETED OPER osed work. If well is direction to this work.) | ATIONS (Clearly state all pertin- cally drilled, give subsurface lo | ent details, and give pertinent cations and measured and true | dates, including estimated date of starting any vertical depths for all markers and sones perti- |
| /8/84 | Advised Rosie with BLM answering service that we intended to cement 2 $7/8$ in well after 11:00 A.M. on $7/9/84$. | | | |
| 7/9/84 | Spear headed 5 Bbls. of water, 43 Bbls of 20-40 Vulcan sand (5000#'s), and 36 Bbls of water. Tagged sand at 4675'. Landed 2 7/8 at 4645'. Mixed 225 sacks Class H cement at 15.6#'s with a yield of 1.18 or 266 cubic feet. Pressure at end of job 2450#'s at 1/4 BPM. Circulated 7 Bbls. of cement. | | | |
| 7/10/84 | Tagged sand at 4430'. Drilled cement thru 4645' and cement/sand from 4668'-4688'. Took bit off to put on notch collar, and seat nipple. | | | |
| 7/11/84 | 1/84 Circulated sand from 4688'-5102' with water. Circulated with nitrofied foam from 5102' to 5270'. Landed tubing at 5202'. Put well in operation. | | | |
| | • | | | ECEIVED JUL 1 8 1984 |
| | | | C | AL CON. DIV. |
| 18. I bereb | y certify that the foregoing is | true and correct | | DIST. 3 |
| SIGNE | D Harry K Bu | TITLE | President | DATE 7/12/84 |
| · | space for Pederal or State offic | e use) | | ACCEPTED FOR RECORD |
| CONDI | TIONS OF APPROVAL, IF A | | CC | JUL 16 1984 |
| | | 14,110 | D C: 1 | FARShipsylver & Service COEA |

*See Instructions on Reverse Side

EY

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the