

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposalsFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 5452

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Federal 19-22-6 1

9. API Well No.

30-043-20343

10. Field and Pool, or Exploratory Area

Rusty Chacra

11. County or Parish, State

Sandoval, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other P&A

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1590' FNL - 1180' FEL
Sec. 19, T22N, R6W, NMPM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐
- Notice of Intent
-
- ☒
- Subsequent Report
-
- ☐
- Final Abandonment Notice

TYPE OF ACTION

- ☒
- Abandonment
-
- ☐
- Recompletion
-
- ☐
- Plugging Back
-
- ☐
- Casing Repair
-
- ☐
- Altering Casing
-
- ☐
- Other _____

- ☐
- Change of Plans
-
- ☐
- New Construction
-
- ☐
- Non-Routine Fracturing
-
- ☐
- Water Shut-Off
-
- ☐
- Conversion to Injection
-
- ☐
- Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was plugged and abandoned on 10/17/96 as follows:

- 1.) TOH. TIH and set CIBP @ 1778'. Cap with 8 sks class "B" cement.
- 2.) POH to 1453'. Spot 55 sks class "B" from 1453-726'.
- 3.) TOH. ND BOP. TIH to 160'. Circulate cement to surface with 18 sks class "B".
- 4.) Cut off wellhead and installed dry hole marker.

Job was witnessed by Marlan Deaton (BLM)

OCT 28 1996

OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed

Title Operations Manager

APPROVED

Date 10/27/96

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

NMOCB

OCT 23 1996
for DISTRICT MANAGER