## UNITED STATES SUBMIT IN TRIPLICATE.

DI	EPARTMEI	NT OF TH	HE INTER	IOR (Other instructions of verse side)	- Γτ~   <u> </u>	5. LEASE DESIGNATION	AND SERIAL NO.	
GEOLOGICAL SURVEY						NM 6674		
(Do not use this form Use	Y NOTICES  for proposals to "APPLICATION	S AND For do on FOR PERMI	REPORTS deepen or plug T—" for such p	ON WELLS back to a different reservoir. proposals.)		S. IF INDIAN, ALLOTTER	OR TRIBE NAME	
OIL GAS WELL OTHER						7. UNIT AGREEMENT NAME		
2. NAME OF OPERATOR Benson Mineral Group, Inc.						8. FARM OR LEASE NAME		
3. ADDRESS OF OPERATOR						Federal 10-21-5		
3200 Anaconda Tower, 555 17th Street, Denver, Colorado 80202						1		
<ol> <li>LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*</li> <li>See also space 17 below.)</li> <li>At surface</li> </ol>						10. FIELD AND POOL, OR WILDCAT Wildcat		
1170' FWL and 1100' FNL Section 10-T21N-R5W						11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA Section 10-T21N-R5W		
14. PERMIT NO.	15.	ELEVATIONS (	ELEVATIONS (Show whether DF, RT, GR, etc.)			2. COUNTY OR PARISH	13. STATE	
		717	'5 GR			Sandoval	N.M.	
<sup>16.</sup>	heck Approp	oriate Box T	o Indicate N	Nature of Notice, Report,	or Oth	er Data		
	E OF INTENTION					T REPORT OF:		
TEST WATER SHUT-OFF	PULL	OR ALTER CASI	ING	WATER SHUT-OFF		REPAIRING W	ELL	
FRACTURE TREAT	MULTI	PLE COMPLETE		FRACTURE TREATMENT		ALTERING CA	SING	
SHOOT OR ACIDIZE REPAIR WELL	SHOOT OR ACIDIZE  ABANDON*  SHOOTING OR ACIDIZING  REPAIR WELL  CHANGE PLANS  (Other)  COUNTY					ABANDONMENT*		
(Other)	CHASG	E PLANS		(NOTE: Report re	mplet	multiple completion of	on Well	
17. DESCRIBE PROPOSED OR COMP proposed work. If well nent to this work.) *	PLETED OPERATIO is directionally	ns (Clearly st drilled, give	ate all pertinen subsurface loca	t details, and give pertinent of tions and measured and true v		on Report and Log for: cluding estimated date lepths for all markers		
6-29-78:	Move in	and rig	up spudde	er. Spud 16:00 6-29	9-78.			
6-30-78:	Set 7" casing at 97' with 50 sacks Class "B" neat, 3% CaCl. Rig down and move out spudder.							
7-1-78:	Move in and rig up B&N Drilling Rig 6.							
7-4-78:	Drilling at 2246'.							
7-5-78:	TD 2275' Plug dow	. Log. 4 n at 05:	½", 10.5# 00 7-5-78	casing set at 226 . Rig released. Wa	53 wit	th 310 sacks of on completic	cement. On unit.	
•						OIL COM. COM.		
18. I hereby certify that the fo	oregoinglis true	and correct						
signed faul C.	Ellison		TITLE P	roduction Manager		DATE July	6, 1978	
(This space for Federal or	State office use							
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:						EGEIVE		
							THE PARTY NAMED IN COLUMN TWO IS NOT THE PARTY N	

JUL 1 0 1978