

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

Jicarilla 54

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Chace Apache

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

Chacon Dakota Assoc.

11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA

Sec. 34, T23N, R3W

12. COUNTY OR PARISH 13. STATE

Sandoval

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR

Chace Oil Company, Inc.

3. ADDRESS OF OPERATOR

313 Washington S.E. Albuquerque, NM 87108

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)

At surface

Unit "K" 1850' SL & 1850' WL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7233 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spudding, etc.

REPAIRING WELL

ALTERING CASING

ABANDONMENT*


(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/2/79 Fenced three sides of reserve pit

6/4/79 Coleman Drilling moved rig in. Spudded well. Drilled 265' 10-3/4" hole. Set 260' 8-5/8" 24# surface casing with 180 sxs Class "B" cement, 3% calcium chloride. Good circulation throughout and circulated cement to surface. Plug down at 10:30 PM

6/5/79 Will drill out from under surface at 10 AM



18. I hereby certify that the foregoing is true and correct

SIGNED

Raymond W. Cary

TITLE

President

DATE

6/5/79

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: