

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☐ well other ☒ Dry Hole  
2. NAME OF OPERATOR  
R. E. Lauritsen  
3. ADDRESS OF OPERATOR  
P.O. Box 832, Farmington, NM 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1750 FSL, 990 FEL, Sec. 8, T21N, R2W  
AT TOP PROD. INTERVAL: R2W  
AT TOTAL DEPTH: 6578 TD  
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:  
TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
NM 7239  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
N/A  
7. UNIT AGREEMENT NAME  
N/A  
8. FARM OR LEASE NAME  
Federal  
9. WELL NO.  
8-21-2-#1  
10. FIELD OR WILDCAT NAME  
Wildcat *Dakota*  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 8, T21N, R2W  
12. COUNTY OR PARISH  
Sandoval  
13. STATE  
NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7159

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

\* Note: Place ~~9.5~~ 9.5 #gal Mud Between Plugs

Plugging Operation: 10 Sacks Cement - Surface - 25'  
35 Sacks Cement - 250'-350'  
35 Sacks Cement - 1000'-1100'  
35 Sacks Cement - 2400'-2500'  
35 Sacks Cement - 5000'-5100'  
50 Sacks Cement - 6400'-TD

Tops from Dual Induction - Laterology

Picture Cliff - - - 1974  
Cliff House - - - 3550  
Point Lookout - - - 4186  
Gallup - - - 5146  
Greenhorn - - - 6235

Graneros "A" - - - 6323  
Graneros "B" - - - 6406  
Dakota D - - - 6495

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. E. Lauritsen TITLE Operator DATE December 1, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED

DEC 11 1980

*Stephen H. ...*  
for DISTRICT ENGINEER