Form 9-331 (May 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

SUBMIT IN TRIPLICATE.

Form approved. Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NM-32359

	GEOLOGICAL SURVEY					
SUNDRY	NOTICES	AND	REPORTS	ON	WEL	LS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

OIL WELL	\mathbf{x}	GAS WELL	OTHER

2. NAME OF OPERATOR

Hanson Oil Corporation

3. ADDRESS OF OPERATOR P. O. Box 1515, Roswell, New Mexico

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

660' FNL & 660' FWL

9. WELL NO.

8. FARM OR LEASE NAME

10. FIELD AND POOL, OR WILDCAT

Candy Butte

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 25, T.17N, R.3W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6365' G.L.

12. COUNTY OR PARISH | 13. STATE Sandova 1

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO: PULL OR ALTER CASING TEST WATER SHUT-OFF MULTIPLE COMPLETE FRACTURE TREAT ABANDON* SHOOT OR ACIDIZE REPAIR WELL CHANGE PLANS

SUBSEQUENT REPORT OF: WATER SHUT-OFF FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL ALTERING CASING

ABANDON MENT

(Other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) •

Plugged and abandoned the above captioned well as follows:

Drilled out CIBP @ 500', 2330', 2400' & 3000' & set cement plugs as follows:

10 sk plug on CIBP @ 3400' to 3270'

35 sk plug from 3150' to 2697'

35 sk plug from 2400' to 1947'

20 sk plug from 400' to 141'

10 sk surface plug with marker

9.2#/gal mud between plugs

Rehabilitated road & location per NTL-6

AUG 13 1981 OIL CON. COM.

P+9 8-26-80

	he foregoing is true and correct	et TITLE	Production Analyst	DATE 9/5/80		
SIGNED	ADDDAVE	TLIS	110330210111111111111111111111111111111	_ DATE		
(This space for Feder	HENNEL	ノ		• * *		
APPROVED BY CONDITIONS OF API	10 h 8 fell	TITLE _		DATE		
	FA JAMES F. SIMS DISTRICT ENGINEER	See Instruction	ons on Reverse Side		. 1 .	