

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR

DOMO PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

501 Airport Drive,
Suite 107, FARMINGTON, NEW MEXICO 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1660' FSL, 1980' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Run Production Casing

☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED


MAR 11 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to 5208'. Ran 149 joints (5193') 4½", 10.5#, K55, ST & C Casing. Casing landed at 5207' K.B. Cemented with 380 sacks 65/35 Pozmix, 4% Gel, and 10# Gilsonite/sack. Followed with 300 sacks Class "B" cement with 10% salt. Plug down at 9:45 A.M. 3/1/80.



MAR 12 1980

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. Hollingsworth
H. D. HOLLINGSWORTH

TITLE Drlg. & Prod. Foreman

DATE 3/8/80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

state