

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

P.O. Drawer 570, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: *1775' FNL & 1030' FWL*

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) *Spud and Casing Report* ☒


☐
☐
☐
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-19-80 Spudded 12-1/4" surface hole at 8:00 P.M. 3-19-80 and drilled to total depth of 200'.

3-20-80 Ran 5 joints (226') of 8-5/8", 24#, K-55 casing set at 236'. Cemented with 140 sacks of Class "B" with 1/4# gel flake per sack and 3% CaCl. Plug down at 6:00 A.M. 3-20-80. Cement circulated to surface. WOC.



Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *[Signature]* TITLE *Dist. Prod. Mgr.* DATE *March 21, 1980*

(This space for Federal or State office use)

ACCEPTED FOR RECORD

CONDITIONS OF APPROVAL, IF ANY:

MAR 25 '80

DISTRICT

*See Instructions on Reverse Side