

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)

Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. NAME OF OPERATOR
RIJAN OIL COMPANY, INC.
3. ADDRESS OF OPERATOR
20 First Plaza, Suite 402, Albuquerque, NM 87102
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
1650' fsl, 2310' fel

14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.)
6727' GR

5. LEASE DESIGNATION AND SERIAL NO.
NM-11772
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N/A
7. UNIT AGREEMENT NAME
N/A
8. FARM OR LEASE NAME
Rijan Oil Company, Inc
9. WELL NO.
Federal 2-26
10. FIELD AND POOL, OR WILDCAT
Wildcat
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 26, T19N, R3W, NMPM
12. COUNTY OR PARISH 13. STATE
Sandoval New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐
REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

P&A well on 5-28-80 in the following manner:

- 1) 5106-5006 w/35 sxs.
- 2) 3920-3820 w/35 sxs.
- 3) 2430-2530 w/35 sxs.
- 4) 1700-1800 w/35 sxs.
- 5) 660-760 w/35 sxs.
- 6) 140-240 w/55 sxs.
- 7) 15 sxs. cement in top of surface casing.

Space between plugs filled w/ 9.2# gal. drilling mud.

Installed regulation dry hole marker. Will clean up location and reseed with required BLM seed mixture. Reseeding to be done in July or August, 1980.

ACCEPTED FOR RECORD

JUN 11 1980

FARMINGTON DISTRICT

BY *[Signature]*

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

Petroleum Engineer

DATE 5-29-80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

[Signature]
JAMES E. GIBB
DIRECTOR OF GEOLOGICAL SURVEY