5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR	NM 17774 로프로 크 원론트
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME 、 多年素物 - も、ままず
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAMES FROM
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME 2 579 B
1. oil gas other	9 WELL NO 9 0 4 5 5 5
2. NAME OF OPERATOR	
DOME PETROLEUM CORPORATION 3 ADDRESS OF OPERATOR 501 Airport Dr.	10. FIELD OR WILDCAT NAME WILDCAT
3. ADDRESS OF OPERATOR 501 Airport Dr. Suite 107, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	ARFA 11.55 : 1.559
helow)	I SEC. 11. TZUN, RZW E = 50 &
AT SURFACE: 2200' FWL, 500' FSL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	SANDOVAL AND NEW MEXICO
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO. 10 10 10 10 10 10 10 10 10 10 10 10 10
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
ner only on onless same	6802 GR 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	to got of top of the control of the
FRACTURE TREAT SHOOT OR ACIDIZE	bn balle
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)과 교실교통
MULTIPLE COMPLETE	* ************************************
ABANDON*	encitanten atago llav stigoat to b mout beniada not benial to stip then o sisb then o sisb then o bolter to b ed bisb
(other) ADDITIONS TO APD	The state of the s
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	
 The BOP pipe rams will be checked daily on trips. 	
The grade of the proposed casing string	32 12 U-40 87 845 5 8 8 8 4
3. The type cement used on the production string: 2 stage (circulated) 65/35 Pozmix with 6% Gel & 10# Gilsonite/sk, followed with class "B" cement with	
Pozmix with 6% Gel & TU# Gilsonite/sk,	followed with class "B" cement with
Pozmix with 6% Gel & 10# Gilsonite/sk, 10% salt. 4. Oil is expected in the Entrada. All o	ther formations are probably water
bearing.	
	mpuntures of phones of the parties o
	State And American
Subsurface Safety Valve: Manu. and Type	Set @ Ft. Ft.
18. I hereby certify that the foregoing is true and correct	
1.0	OPEMAN - Februari 8 1980 COM.
SIGNED ALLEN STATE TITLE DRLG & PROD FOREMANDATE FEBRUARY 8, 1986	
(This space for Federal or State of	ffice use) # 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
APPROVED BYTITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	
	Beneral dependency of the property of the plant of the pl
	The state of the s

*See Instructions on Reverse Side

take