REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON*

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Dec. 1973	Budget Bureau No. 42-R1424		
UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE NOO-C-14-20-5044 6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME		
1. oil gas well other	8. FARM OR LEASE NAME Dome Navajo 28-22-6 9. WELL NO.		
2. NAME OF OPERATOR Dome Petroleum Corp.	2 10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR 501 Airport Drive,	Rusty Chacra Extension		
Suite 114, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1780' FSL, 830' FEL AT TOP PROD. INTERVAL:	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 28, T22N, R6W 12. COUNTY OR PARISH 13. STATE Sandoval New Mexico		
AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.		

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

6947' GR

(other) Run Production Casing 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and

SUBSEQUENT REPORT OF:

measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 54 jts. (2219') 45", 10.5#, K55, ST&C Casing. Casing landed at 2219' GL. Cemented with 175 sacks 65/35 Pozmix with 6% Gel and 10# Gilsonite/Sack. Followed with 125 sacks Class "B" Cement with 2% CaCl. Plug down at 5:45 a.m. 9/10/80. Circulated cement.

RECEIVED

SEP 1 9 1980

U. S. GEOLOGICAL SURVEY FARMINGTON, N. M.

SEP 24 1980 OIL CON. COM. DIST. 3

10	I hereby certify that	t the foregoing is	true and aceroal

Subsurface Safety Valve: Manu. and Type __

TITLE Drlg.&Prod.Foremanbate September 17,

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

35

ACCEPTED FOR NECUKI

SEP 2 3 1980

*See Instructions on Reverse Side

ARMINGTON DISTRICT